

# SCIENTIFIC AMERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter.]

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES.

Vol. LVII.—No. 2.  
[NEW SERIES.]

NEW YORK, JULY 9, 1887

[\$3.00 per Year.]

## RAISING A SUNKEN STEAMSHIP.

Those who have had occasion to cross the Jersey City or Hoboken ferries may have noticed a collection of nondescript craft anchored in the North River, well over toward the New Jersey shore, yet quite distant from it. Coming down the river or up from the bay, the group looked not unlike a swarm of big flies gathered about a dead beetle lying on its back with stiffened legs projecting up into the air. Near by, the mainmast of a submerged ship is readily made out, and the accompanying craft seen to be great box-shaped boats, some of them a hundred feet long, and in company a full-rigged schooner. The sunken vessel is the British steamer Welles City, and the craft about her the property of the Merritt wrecking organization, which has been engaged in raising her.

On a stormy afternoon in the early part of last February, the Welles City steamed up the Hudson River as far as Christopher Street, well over toward Jersey City, and dropped anchor.

The captain had chosen his anchorage with an eye to convenient delivery of cargo rather than to good holding ground, because, under ordinary conditions, there is not much strain on the cables of a ship riding at anchor in the smooth waters of a riverway; and so it was that when, toward daylight, a huge field of ice, having broken away, suddenly came pounding down upon him, he was wholly unprepared. His bower anchor tore its way through the soft mud of the bottom and was soon afoul. The holding fluke tripped, and permitted the anchor to fall over on to its side; and though he quickly dropped his big kedge anchor, whose

broad stock or cross-bar prevents its fouling, the power of the mud to resist was not equal to the force of the oncoming ice, and the Welles City went drifting down stream. Directly in her track lay anchored the iron steamer Lone Star, of the Morgan line. She headed in the direction whence the Welles City was advancing, and, her crew perhaps not wide-awake nor quick enough to slip their cables, the Welles City came down upon the sharp iron prow of the Lone Star broadside on. It cut into her side just abaft the main channels as though she had been made of cheese, and giving a great list, she rocked forward and aft several times, and went to the bottom in eight fathoms of water.

On the other side of the world they are content, when a large vessel goes down in navigable waters, to take

(Continued on page 23.)



RAISING THE STEEL STEAMSHIP WELLES CITY, HUDSON RIVER, N. Y.—PONTOONS AND SLINGS IN POSITION FOR WORK.



# Scientific American.

ESTABLISHED 1845.

MUNN &amp; CO., Editors and Proprietors.

PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

A. E. BEACH.

## TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year, for the U. S. or Canada.....\$3 00  
 One copy, six months, for the U. S. or Canada..... 1 50  
 One copy, one year, to any foreign country belonging to Postal Union, 4 00  
 Remit by postal or express money order.

**Australia and New Zealand.**—Those who desire to receive the SCIENTIFIC AMERICAN, for a little over one year, may remit \$1 in current Colonial bank notes. Address

MUNN &amp; CO., 361 Broadway, corner of Franklin Street, New York.

## The Scientific American Supplement

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for U. S. and Canada. \$5.00 a year to foreign countries belonging to the Postal Union. Single copies, 10 cents. Sold by all newsdealers throughout the country.

**Combined Rates.**—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, to any address in U. S. or Canada, on receipt of seven dollars.

The safest way to remit is by draft, postal order, express money order, or registered letter.

**Australia and New Zealand.**—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for a little over one year on receipt of \$2 current Colonial bank notes.

Address MUNN &amp; CO., 361 Broadway, corner of Franklin Street, New York.

## Scientific American Export Edition.

The SCIENTIFIC AMERICAN Export Edition is a large and splendid periodical, issued once a month. Each number contains about one hundred large quarto pages, profusely illustrated, embracing: (1) Most of the plates and pages of the four preceding weekly issues of the SCIENTIFIC AMERICAN, with its splendid engravings and valuable information. (2) Commercial, trade, and manufacturing announcements of leading houses. Terms for Export Edition, \$5.00 a year, sent prepaid to any part of the world. Single copies, 50 cents. **Manufacturers and others who desire to secure foreign trade may have large and handsomely displayed announcements published in this edition at a very moderate cost.**

Address MUNN &amp; CO., 361 Broadway, corner of Franklin Street, New York.

NEW YORK, SATURDAY, JULY 9, 1887.

## Contents.

(Illustrated articles are marked with an asterisk.)

Batteries, primary, economical disposition of.....	16	Keyhole guide and escutcheon.....	16
Books and publications, new.....	20	Larva of bot fly in horse's stomach.....	20
Business and personal.....	20	Lathe, wood turning, automatic.....	18
Butter, artificial, identification of.....	24	Mill to free rice from its hulls.....	18
Butterflies, to catch and preserve.....	24	Moths, how to catch.....	24
Camera, photographic, simple.....	24	Notes and queries.....	27
Carpet sweeper, dust controlling.....	24	Patents, stability of.....	27
Cotton planter, device to feed the seed in.....	18	Pen for double and single line ruling.....	10
Cruiser Le Terrible, armored, French.....	29	Petroleum, exhaustion of.....	20
Eggs, raw, do not eat.....	18	Photographic and photo-micrographic apparatus, simple.....	25
Elephant, notable, death of.....	20	Photographs, instantaneous, new light for.....	17
Employer's liability.....	17	Photography in natural colors.....	17
Engine, cut-off, automatic.....	21	Photography of projectiles.....	24
Engine, steam, in 1880.....	21	Photometry, curiosity in.....	25
Fibers, animal and vegetable, test for.....	20	Pia.....	25
Food adulterations.....	20	Repeating, a new.....	19
Furniture, wall protecting attachment for.....	19	Resin in soap and fats.....	21
Fuse cutter and cap setter.....	19	Roburite, the new explosive.....	21
Gold on Alaska island.....	19	Ships, war, French.....	21
Industrial Union, accession of United States to.....	16	Siren in marine signaling, use of.....	16
Inventions, engineering.....	21	Slate, uses of.....	17
Inventions, index of.....	21	Steamship, sunken, raising.....	15
Inventions, miscellaneous.....	21	Stool and chair, folding.....	19
Ironing machine, steam heated.....	21	Thermometer, new style of.....	20
Items of interest, many.....	20	Tin, coppered.....	21
		Water gauge float, improved.....	19

## TABLE OF CONTENTS OF SCIENTIFIC AMERICAN SUPPLEMENT No. 601.

For the Week Ending July 9, 1887.

Price 10 cents. For sale by all newsdealers.

I. ASTRONOMY.—A Star Finder.—A simple apparatus that can be constructed by any mechanic.—1 illustration.....	9006
Photographic Study of Stellar Spectra, Harvard College Observatory.—First annual report of the Henry Draper memorial observations.—Review of the work by Prof. EDWARD C. PICKERING.....	9008
II. BIOLOGY.—Sponges.—The growth and life history of sponges.—Report of a recent lecture at the London Royal Institution by Dr. R. VON LIEBENFELD.....	9005
III. ELECTRICITY.—Phenomena of Alternating Currents.—By Prof. ELIUS THOMSON.—15 illustrations.....	9001
IV. ENGINEERING.—An English Car Coupling.—Description of an English automatic coupling.—2 illustrations.....	9008
A New Process of Casting Iron and other Metals upon Lase, Burchard, Fern Leaven, and other Combustible Materials.—By A. E. OUTERBRIDGE, JR.—A new and eminently practical process of producing ornamental castings.—4 illustrations.....	9006
Bricks and Brick Work.—By Prof. T. ROGER SMITH, F.R.I.B.A.—The history and technical review of this subject.—A most remarkable contribution to the engineering of architecture.....	9006
Link Belting.—By CHARLES A. SCHERER.—An interesting and practical paper on leather belting made of links.—9 illustrations.....	9005
Recent Progress in Gas Engineering.—A lecture by Mr. A. MACPHERSON, of Kirkcaldy, reviewing the last improvements in this branch.....	9006
V. MISCELLANEOUS.—Herbert's Tepid Douche.—Apparatus in use for bathing soldiers in the French barracks.—1 illustration.....	9006
Kent's Torsion Balance.—A new type of balance, involving torsional suspension instead of knife edges.—5 illustrations.....	9004
Preservative Liquid.—Note on preservation of organic substances.....	9004
The Falls of Gairn.—The great Indian falls, higher than Niagara.—5 illustrations.....	9006
The New British Coinage and Jubilee Medal.—Illustrations and descriptions of the new pieces.—6 illustrations.....	9008
The Winner of the Derby.—Portrait and description of Merry Hampton.....	9004
VI. NAVAL ENGINEERING.—The Falke Type Torpedo Boat.—The fastest type of British torpedo boat, constructed by Messrs. Yarrow & Co.—1 illustration.....	9001
The German Navy.—The New Gunboat Wier.—A description of a late accession to the German navy.—1 illustration.....	9001
VII. ORDNAVANCE AND GUNNERY.—Magazine Rifles.—Continuation of this important article, including the Chaffee-Roscoe, Kropatschek, and other magazine guns.—5 illustrations.....	9006
New British Torpedo Experiments.—Experiments with torpedoes against a ship.—The efficiency of torpedo nets.—The effects of Whitehead torpedoes.....	9002

## ACCESSION OF THE UNITED STATES TO THE INDUSTRIAL UNION.

The following announcement is made in *La Propriete Industrielle*, the official organ of the International Bureau of the Union: "From a communication addressed to the Federal Council of Switzerland by the United States minister at Berne, the date of the accession of the United States to the Union for the protection of industrial property has been fixed for May 30, 1887." According to the above, the United States is now a member of the Union, and our citizens are entitled to the enjoyment of all its benefits. The fact, we presume, will be soon proclaimed by the President.

It is difficult at the present time to foresee all the results, advantageous or the contrary, that may accrue to us from this membership. It has been very extensively published in the daily press that, under the laws of the Union, all American patentees would enjoy a priority of time for seven months after the date of their American patents, during which they could take patents in all the several countries covered by the Union. But this is an error, as the laws of the Union provide for a priority of seven months, not from the date of the patent, but from the date of the application for the patent.

As the business of our patent office is considerably in arrears, in some classes more than seven months in arrears, in such cases the Union affords no benefit. In other classes the arrearage is not more than two or three months. In these cases the Union will be of some benefit.

The other laws of the Union relate chiefly to trade marks, concerning which the protection accorded to the members of the Union is full and satisfactory.

The following are the present members of the Industrial Union: Belgium, Brazil, Spain, France, Guatemala, Italy, the Netherlands, Portugal, Salvador, Serbia, Switzerland, Great Britain, Mexico, Sweden, Norway, Paraguay, Uruguay, Roumania, Tunis, the United States.

In the official statement of the articles of the convention, published in the *Patent Office Gazette* of May 24, 1887, it was stated that Germany was a member of the Union; but this we believe to be an error. Germany, we are informed, has not yet become a member.

## USE OF THE SIREN IN MARINE SIGNALING.

In certain cases, as in fogs and tempests, optic telegraphy is impossible. Cannons have long been employed in these cases. A slightly violent wind makes them nearly useless, and even in good weather they are of little use, because of the difficulty of sufficiently multiplying their detonations, as to whose number there are no certain and invariable agreements.

As for the ordinary whistle, these can only serve as toys, and could they be employed in signaling, the steam whistle, already much used, would be preferable. Here, too, the lack of agreement as to meaning of signals operates to restrict their use.

For some little time, ocean vessels owned by the large shipping companies have been provided with an instrument giving sounds of wonderful height and intensity. We speak of the siren. The siren, invented by Cagnard de la Tour, has been greatly modified, and steam has replaced the original currents of air. Applied to the same uses, the siren leaves far behind it the cannon, ordinary whistle, and steam whistle. Nothing remains but to fix a certain and invariable standard of comparison.

We give below the ideas emanating from M. Edme Genglaire, student of the naval school of medicine at Toulon.

The siren being in communication with the boiler, the current of steam can be governed by an ordinary valve. The sounds produced vary in height and intensity in proportion to the quantity of steam emitted, so that sounds of any given pitch can be obtained. A set of resonators completes the apparatus.

It is well known that two identical resonators vibrate together for the same sound and for that only. Starting with this principle, in two similar frames containing several resonators, the corresponding resonators will vibrate or sound only when the note corresponding to them is produced. The siren will produce these sounds causing vibrations in the resonators, and two distant ships, or a shore station and a ship, or two land stations, supplied with sirens of similar model and identical frames of resonators, could most conveniently communicate. For this end each resonator should have attached to it an invariable signification, the same for all the frames.

All the navy and commercial vessels possessing sirens and a frame carrying the same number of resonators, each marked with a number having its signification, will be prepared to communicate with each other or with the shore. It must be remembered that these acoustic effects can be conveyed intelligibly to an immense distance by the aid of the siren and the additional apparatus. The apparatus, moreover, does not cost much for establishment.

The preceding theory being admitted, the following is the practical way of carrying it out as proposed by M. Genglaire:

In front of each resonator will be placed two metallic reeds; one rigid, the other thin and producing extended oscillations with the least effort. Each of these pieces of steel communicates with one pole of a battery by means of the circuit wire. When the resonator vibrates, the thin reed oscillates, touches the other bar, and the two poles of the battery being connected, an electric bell rings, thus giving a signal, so that the call, whether from ship or shore, can be recognized, while the bell of the signaling station by its sounds shows that the desired vibration or note has been produced. —*Electricite.*

## THE ECONOMICAL DISPOSITION OF PRIMARY BATTERIES.

The true action of a primary galvanic battery in some of its features is not generally comprehended, even by those familiar with the ordinary phenomena of electricity. The size of a battery, and the direct effects of varying it, and the deleterious effects of internal resistance, are among the factors least grasped. At the present day the error is sometimes made of supposing that the size of a cell affects its electromotive force, and internal resistance is often spoken of as a beneficial element.

Yet if the subject be brought down to facts, the case is a very clear one. The electromotive force is quite independent of dimensions, and a cell the size of a percussion cap will produce as high electromotive force as the largest made. This, to many, sounds a truism, yet it is by no means universally realized. But on the subject of resistance a more firmly fixed misconception prevails to a considerable extent. It is often asserted that low resistance batteries are not wanted. The truth is that they are wanted, and that the invention of a non-polarizing or constant and low resistance battery would be a valuable contribution to the resources of the electric engineer. The source of the error on the subject of resistance is doubtless due to the universal application of Ohm's law for fixing the number of cells in a battery for given external resistance.

By simple mathematical demonstrations it is proved that the most economical distribution of battery, as far as the number of cells is concerned, is attained when the internal, or battery, resistance and the resistance of the external circuit are equal. Thus with ten ohms resistance on the outer circuit, enough cells should be provided to have the same resistance internally. This, however, refers only to the number of cells, and not to their economic working. This limitation is very generally overlooked. The arrangement of battery so as to make internal and external resistance the same is considered the ultimatum, and the low resistance of cells is held not to be a specific advantage.

The ordinary calculation of the number of cells required to supply a circuit may be used as an example. Suppose a difference of potential of 35 volts is to be maintained between the extremities of an external circuit of 40 ohms resistance, giving a current of 0.875 ampere, and assume each cell of the given battery to yield 1.75 volts with an internal resistance of 1 ohm. In making the calculation, it is at first taken for granted that the internal resistance of the battery must be 40 ohms. Therefore the total resistance to be overcome is 80 ohms, so that the effective voltage of the battery is reduced one half. Dividing, therefore, 35 volts by 0.875 volt, the dividend 40 is the number of cells that must be arranged in series. Then, as these will have a resistance of 40 ohms, the problem is solved, and this is treated as the most advantageous possible arrangement. This it is far from being; it is the best arrangement of forty elements in the given circuit. It contains the minimum number of elements that will maintain the given current through the circuit, but it is not an economical arrangement as regards consumption of material.

The battery in the case cited having exactly the same resistance as the external circuit, absorbs one half of the current. One half of the electrical energy disappears in forcing the current through the battery. This represents fifty per cent of the chemicals and zinc which is actually wasted or spent on useless work. A battery run on this principle by no fair principle can be compared with a steam boiler, to settle the point of efficiency. It is doing only a shade over half the useful work that it is capable of. To compare the cost of a battery with any other prime generator, it must work under widely different circumstances from that instanced. Its difference of potential, and at the same time its resistance, must be lowered. This can be done by increasing the number of elements and arranging them in several parallel series.

The battery and circuit above cited having a resistance of 80 ohms with 70 volts difference of potential in the battery, maintains a current of 0.875 ampere. By arranging four such series of cells in parallel, the internal resistance would be reduced to 10 ohms, the total resistance to 50 ohms, and a current of 1.4 ampere would be produced. To reduce this to 0.875 ampere, four parallel series of twenty-three cells each would be required. This is an increase in cells. The total number is 92 instead of 40. But as the battery would only have one seventh the resistance of the whole circuit, it would absorb one seventh instead of



one half the electrical energy, thus indicating at once a saving of nearly 50 per cent in consumption of zinc and chemicals. The limit of efficiency is approximated to by using a little over double the original number of cells.

In all applications of primary batteries to motors, this principle should be kept in mind. In storage batteries it has received a high development. They have such low internal resistance that it is treated as of no value, or as zero. It is for this reason that they have become of no practical value. Were they of high resistance, and were they used so as to possess within themselves one half the total resistance, then, instead of developing an electric efficiency of 85 to 90 per cent, they would give a return of only  $42\frac{1}{2}$  to 45 per cent of the charging current. Their constructors in order to obtain a commercial efficiency were obliged to construct them of low resistance. But the inventors of primary batteries having their minds fixed on other considerations, such as economy of space, rather than economy of material consumed, have overlooked the evil effects of high resistance.

The resistance may be reduced by bringing the plates closer together. In the primary battery the solution of a metal has to be provided for, and the difficulties due to the low rate of diffusion of liquids have prevented too near an approach of the plates to each other. In the storage battery this trouble is of course absent. But it is clear that in low resistance lies the hope for a future use of the primary battery for small powers or for electric launches. So many points tell in favor of the primary battery that it seems a pity that it cannot be more generally used. But it can never be economically employed if the minimum number of cells only is adopted as the basis of installment.

#### Photography in Natural Colors.

A very remarkable chemical paper by M. Cary Lea is now in course of publication in the *American Journal of Science*, in which the author gives the results of his laborious and extensive investigations concerning the salts of silver and their relations to the photographic image. The ease with which the author produces the most splendid colors, their richness and variety, is really marvelous. He reaches the gratifying conclusion that photography in natural colors is now among the possibilities of science. We give a few extracts from the concluding portions of his paper:

Almost any silver solution brought into contact with almost any reducing agent, and then treated with HCl, gives rise to the formation of photo-chloride. Almost any chlorizing influence brought to bear on metallic silver has the same result. Or when silver is brought into contact with almost any oxidizing agent and HCl, it may be said without exaggeration that the number of reactions that lead to the formation of photo-chloride is much larger than that of those leading to production of normal chloride.

Exposed to ordinary diffused light, all the bright shades of silver photo-chloride quickly change to purple and purple black. The darker shades are more slowly influenced.

Mercuric chloride gradually changes it to a dirty white.

Mercuric nitrate dissolves it easily and completely, but apparently with decomposition, as it can only be recovered as white chloride.

Potassic chloride seems to be without effect.

Potassic bromide soon converts it to a dull lilac, which at the end of twelve hours showed no further change.

In contact with potassic iodide, the color instantly changes to blue gray; this change is produced by a quantity of iodide too small to dissolve even a trace of silver; the filtrate is not darkened by ammonium sulphide. With a larger quantity, silver is dissolved abundantly. By acting with renewed iodide solution, the substance continually darkens and diminishes until only a few black points, barely visible, are left.

Treated with dilute solution of potassium chlorate and HCl, the red substance gradually passes to pink, to flesh color, and finally to pure white.

The action of heat on the photo-chloride is very curious; its tendency is generally toward redness. Specimens appearing quite black are rendered distinctly purple or chocolate by heating to  $212^{\circ}$  Fah. in a drying oven. Often when the substance first separates by addition of HCl, it is pure gray; this gray will often be changed to pink by simply heating to  $212^{\circ}$ . (This happens when a gray form is produced; if the grayness is due to admixed metallic silver, it is only removed by boiling with nitric acid.)

The somewhat surprising change of color which is often seen when the crude substance is boiled with nitric acid (sometimes from dull dark gray to crimson) is due to three concurrent actions—that of the mere heat, the removal of the silver, and the breaking up of uncombined subchloride.

#### RELATIONS OF PHOTO-CHLORIDE TO HELIOCHROMY.

The photo-chloride was examined both with the spectrum and under colored glass.

The rose colored form of photo-chloride was that which gave the best effect. In the violet of the

spectrum it assumed a pure violet color, in the blue it acquired a slate blue, in green and yellow a bleaching influence was shown, in the red it remained unchanged. The maximum effect was about the line F, with another maximum at the end of the visible violet, less marked than the one at F.

Under colored glass the colors obtained were brighter; under two thicknesses of dark ruby glass the red became brighter and richer. Under blue glass some specimens gave a fair blue, others merely gray. Under cobalt a deep blue was easily obtained, and under manganese violet a fine violet, very distinct in shade from the cobalt. Green produced but little effect; yellow was sometimes faintly reproduced, but rarely. But the yellow glass of commerce, even the dark yellow, lets through portions of nearly the whole spectrum, as can readily be seen by testing it with the spectroscopic.

The dark purple forms of chloride do not give as good results as the rose and coppery shades. These last have many points of resemblance with the material of Becquerel's films—resemblance of color, probably of composition, as far as we can judge of the constitution of those films from their origin; they were far too attenuated to admit of analysis; and resemblance in the curious way in which their color is affected by heat, so that the conclusion seems inevitable that they are at least closely related.

There is certainly here a great and most interesting field for experiment; hardly any two specimens of photo-chloride give exactly the same results with colored light, and this suggests great possibilities. There is the very great advantage in this method over any previous, that the material is easily obtained in any desired quantity, and in a condition most favorable for experiment.

The action of light on proto-chloride can be a good deal affected by placing other substances in contact with it. Any substance capable of giving up chlorine seems to influence the action somewhat; ferric chloride often acts favorably, also stannic and cupric chlorides.

Evidently an important point in all heliochromic processes is that as white light must be represented by white in the image, it is an essential condition that white light must exert a bleaching action on the sensitive substance employed. Red chloride does not bleach but darkens in white light, but the property of bleaching, to a very considerable extent, may be conferred on it by certain other chlorides, and particularly by lead chloride and zinc chloride.

This I look upon as very important.

Another matter of interest is exaltation of sensitiveness, and this I find is accomplished in quite a remarkable way by sodium salicylate, the presence of which at least trebles the action of light on these substances, and probably on others.

I am persuaded that in the reactions which have been here described lies the future of heliochromy, and that in some form or other this beautiful red chloride is destined to lead eventually to the reproduction of natural colors.

#### Employers' Liability.

In many cases of injury to workmen running machinery, it is difficult to decide which party is to be held responsible, or whether it is attributable to mere unavoidable accident, which it was impossible to caution or guard against. Each of the parties wants to shift the responsibility upon the other, the employee to recover damages from the employer, and the latter to shirk such obligation. Where the case is not quite plain, or is not settled by compromise, endless lawsuits are frequently the consequence. The legislative bodies of the various States and of all industrial countries have endeavored, therefore, to define the liability of employers; and building inspectors, factory inspectors, boiler inspectors, and a number of other similar functionaries have been appointed to see that the laws are observed and that the regulations regarding precautionary measures to prevent accidents in factories are complied with. But the more numerous and the more specialized such enactments become, the less security they afford to the parties concerned, and the wider a field do they open for legal trickery and the more loopholes for evasion.

The fact is, the very oldest part of our common law affords the best common sense as to the proper standpoints for judging of such liability, and there is perhaps more danger that legislators will, by statute, limit and impair the efficacy of the common law than that they will improve upon it by newly devised regulations. The English government has lately been collecting information as to the law in relation to this matter in other countries, and the reports seem to confirm the idea that in no other country are the provisions of the law so generally sound and wholesome as in France. All such questions in France are still regulated by common law, and its provisions concerning them are thus formulated by the civil code:

ART. 1382. Any action whatever of a man which causes an injury to another obliges the person by whose fault the injury has occurred to repair it.

ART. 1383. Everybody is responsible for the injury he has caused, not only by his action, but also by his negligence and imprudence.

ART. 1384. A man is responsible, not only for the injury he has caused by his own action, but also for that which is caused by the action of persons for whom he is answerable, or of things in his charge.

The father, or the mother, after the decease of the husband, are responsible for the injury caused by their children [here the Roman law has: also guardians for injuries caused by their charges.—ED.] who live with them, being minors.

Masters and employers for the injury caused by their servants [Roman: slaves] and overseers in the performance of the functions in which they have employed them.

Tutors and artisans for the injury caused by their pupils or apprentices during the time they are under their supervision.

This responsibility is incurred unless the father, mother (guardian, masters, and employers), tutor, or artisan prove that they could not prevent the action which gives rise to the responsibility.

ART. 1385. The owner of an animal, or the person using it, is responsible, so long as it is being used by him, for the injury which the animal has caused, whether the animal was in his charge or whether it had strayed or escaped.

ART. 1386. The owner of a building is responsible for the damage caused by its fall, when such fall has taken place in consequence of defective maintenance or faulty construction.

The principles laid down in these articles are almost verbatim translations of the Roman law, and are also nearly in the same wording contained in the old Prussian "Landrecht" compiled by Suarez, under the reign of Frederick II. They would undoubtedly be held as good common law in all our courts to-day, where not limited by some statute. They include, in fact, all cases of responsibility imaginable, and our law makers have actually nothing more to do than to make regulations in reference to the use of steam power and machinery, whose violation puts the owner, employer, or overseer in a position of responsibility analogous to the owner of a building, animal, slave, etc., after the Roman law.

#### Uses of Slate.

Slate is not confined to its use as a roofing material by any means, but, on the contrary, is probably more universally used than any other stone. In composition and texture, it is admirably adapted to the reception of carved and moulded designs, is susceptible of a high polish, and possesses great power of resistance to the principal destructive elements, besides having the additional merit of wide range of color, embracing black, dark blue, purple, purple clouded green, gray clouded green, light green, and a clear, bright red. The scope of consumption is rapidly expanding, and among the uses to which slate is applied the following may be enumerated: Flagging, flooring, floor tiles, moulding for tiles, vestibule trimmings, slabs, etc., wainscoting, mantels, hearthstones, steps, risers, platforms, sills and lintels, turned balusters, laundry and bath tubs, sinks and wash trays, meat and water tanks, refrigerator and cooling room shelves, cistern linings, brewers' vats, mangers, butchers' and curriers' tables, bar fixtures, billiard table beds, urinals, school slates and blackboards, countertops, vault work, grave linings and covers, and memorial tablets. Of the above, no record of production or value can be obtained that would prove at all useful as a basis for estimates. Possibly, a faint idea of the proportions devoted to these various uses might be obtained from the production of the Slatington (Pa.) section, where, besides an output of 108,000 squares \* of roofing slate, there were also made (in 1885), in round numbers, 39,900 cases of school slates, 21,850 pieces, or 1,430 cases, or 27 carloads, of flagging, 5,900 cases of blackboards, 30 cases of mantels and hearths, and 47 car loads of shaved slate.—*Mineral Resources of United States*.

#### A New Light for Instantaneous Photographs.

At a recent meeting of the Berlin Physical Society, Prof. C. W. Vogel communicated the most recent discovery in connection with instantaneous photography, by which it is now possible to obtain instantaneous photographs not only at night, but also in the darkest places. Messrs. Goedicke and Miethe have prepared a mixture of pulverized magnesium, chloride of potash, and sulphide of antimony, which when ignited produces an explosive, lightning-like illumination of such intensity that by means of it an instantaneous photograph can be taken. The speaker then gave a demonstration of the discovery by taking photographs of several persons present. He used the artificial light, of which each flash lasted one-fortieth of a second, and in a few minutes produced a picture during the meeting. The powders, as prepared by the discoverers, cost only a few pfennigs each, and will hence readily come into general use.


\* A "square" is 100 square feet, weighs 600 lb., and covers the same area as 1,000 shingles.



#### A MILL TO FREE RICE FROM ITS HULLS.

The invention herewith illustrated, which has been patented by Mr. John A. Lockfaw, of Wilmington, N. C., provides a mill designed to receive the rice as it comes continuously from the thrashing machine, and separate the grains or kernels of rice from the hulls. The central operating shaft is hollow, and as the rice is fed down the hopper it is carried along the inside of this shaft by a spirally flanged conveyer, shown in dotted lines, and delivered in the center of the casing at the opposite end of the shaft, the shaft carrying upon this end a disk with roughened surface. Just in front of this disk, and held at its edges by the flanges of the two sections of which the casing is made, is a flexible diaphragm, preferably made of heavy canvas. At the rear of this diaphragm, and opening centrally into the chamber in which it is situated, is a tube connected with an air pump operated by an eccentric on the main shaft, so that as the latter revolves, and feeds the rice forward from the hopper delivering it between the roughened disk and the diaphragm, there will be an air pressure at the back of the latter. This diaphragm is intended to be sufficiently yielding to prevent the rice from being broken as it is caught between the roughened face of the disk and the diaphragm, by which the hulls are stripped from the kernels of the grain; and in order to prevent too high an air pressure being kept up in the chamber, a safety valve is provided in the top of the casing, through which the pressure is regulated by the tension of a spring. There is also mounted upon the shaft a pulley which drives a fan, the blast from which is delivered in front of an opening near the bottom of the casing, out of which the rice and hulls fall when the mill is in operation, the hulls being thus

ironing is effected by the hollow metallic rollers shown, which are operated by a belt from any convenient power, the journals of the rollers being tubular, for the entrance and escape of the steam necessary for properly heating the rollers, and any desired pressure is obtained by turning the small crank handles shown.



ROHLMANN'S WOOD TURNING LATHE.

For further information address the patentee, Mr. Frank Corbett, No. 354 Bowery, New York City.

#### AN AUTOMATIC WOOD TURNING LATHE.

It will be readily understood from the illustration how the power communicated through the driving pulley operates the lathe spindle and its mandrel, and the worm on the same shaft, through which motion is imparted to the sprocket chain seen in front, which moves the tool carriage. The latter is adapted to slide on guideways on the main frame, and carries two adjustable tools. It also has an upper and a lower pocket, through which pass the upper and lower parts of the sprocket chain, engagement of the tool carriage with either part of which—thus giving the backward and forward movement—is effected by the engagement of arms on the tool carriage with tripping arms on the main frame.

The rear part of the tool carriage actuates a feeding mechanism for placing the wood to be turned automatically in the lathe between the mandrel on the operating shaft and the opposite end centering spindle, the feeding mechanism being supported upon ways secured to the main frame, which also support a rack or hopper, in which the wood to be turned is placed. As shown in the illustration, the block to be turned is held by the feeder in position to be grasped and held between the end spindle and the mandrel on the shaft of the driving pulley. The forward motion of the tool carriage effects this by disengaging a pivoted latch, when a weighted bell crank lever throws the spindle forward, the spindle taking hold of one end of the block, while forcing the other end centrally on the mandrel opposite, and the block is rotated by the operating spindle. At the same time the movement of the tool carriage turns a forward projecting rod of the feeder, which had acted as an arm to hold the block in position, thus releasing the block, and, by another lever, the carriage which had fed the block up into position is caused to slide backward till its front is directly under the rack or hopper, when another block of wood slides down upon it.

As the tool carriage moves to the left, the cutting tools, properly adjusted, finish the turning of the block, when the chuck on the tool carriage comes in contact with the one on the operating mandrel, pushing the latter to the left, thereby disengaging one end of the turned block, and raising a weight which holds the mandrel in locked position, while a lug of the tool carriage operates a bar that forces the spindle at the other end to slide backward, disengaging the other end of the turned block, which then drops out of the machine.

On the backward motion of the tool carriage, a lug thereon engages a lever which causes the feed carriage to slide forward, with the new block of wood to be operated upon held in position to be engaged by the mandrel on the operating shaft and the opposite spindle, as at first. The tools are easily adjusted or changed, their position on the top of the tool carriage rendering them readily accessible, and the special manner in which the feeding mechanism is supported and operated holds its devices and the blocks being fed well out of the way, so that they will not interfere with the free working of the other parts of the machine.

This invention has been patented by Mr. Joseph Rohlmann, of 3001 Messaine Street, St. Joseph, Mo.


#### Do not Eat Raw Eggs.

In the *Monatschrift zum Schutze der Vogelwelt*, Professor Liebe adduces reliable data in answer to the question whether living worms are to be found in hens' eggs. A short time previously his sister had found a round, thread-like worm, the length of a little finger, in the white of an egg. It moved itself in a very lively manner. She at once took the white of the egg to a druggist, who put the worm in alcohol. Professor Mobius, of Kiel, decided that the specimen was an example of the thread worm of fowls—*Heterakis inflexa*—often found in the small intestine of the domestic hen. Only a few instances of the existence of the same in the white of the egg have been recorded.—*Allgemeine Medicinische Central-Zeitung*.

#### A MINER'S TOOL TO CUT FUSES, SET CAPS, ETC.

The invention herewith illustrated provides a combination tool for miners' use, to cut the fuse, fasten the cap thereon, and to make a cavity in the powder, when desired, for inserting the fuse and cap, preparatory to its being fired. Near the pivot connecting the blades of the plier like tool are half round openings or slots having curved cutting edges, by which the fuse can be squarely cut into two parts. Near the front end of the tool are half round openings having inwardly projecting flanges or prongs, and when the firing cap is slipped over the cut-off end of the fuse, and the tool applied thereto, these prongs embed themselves in the thin metal forming the sides of the cap and firmly clinch it to the fuse. Within the handle is pivoted a pin, which can be readily swung out, as shown in dotted lines, and forms a serviceable tool for making a proper cavity for the fuse in the powder.

For further particulars relative to this invention,




HALE'S FUSE CUTTER AND CAP SETTER.

address Mr. C. D. Hale, patentee, or Mr. F. H. Cole, box 377, Leadville, Col.


#### A DEVICE TO FEED THE SEED IN COTTON PLANTING.

Our illustration shows a hopper and seed feeding device therein which has recently been patented by Mr. Charles W. Oldham, of Mitchell, Ind. At or near the front of the hopper is journaled the crank shaft for operating the feed, the crank itself not being shown in our view, the shaft carrying a drum, and a block being attached to the shaft by cheek pieces. Connected to this block by a right and left hand screw rod is a similar block with cheek pieces, in the outer ends of which is journaled another shaft, carrying also a



OLDHAM'S FEED FOR COTTON PLANTERS.

drum, the distance apart of the shafts being adjusted by turning the screw rod. Over the drums thus carried by these shafts is placed a feed belt carrying outwardly projecting teeth, which, as the crank handle is revolved, carry the seed from the hopper over a low projection secured to the front end of its bottom. The hopper is filled with seed by lifting out the frame and feed belt to the position shown in dotted lines, and in operation the belt and frame rest upon the mass of seeds, feeding from the upper surface and lowering in the hopper as the mass diminishes.




LOCKFAW'S RICE MILL.

blown off. It is said that this mill works well practically, and exceeds the anticipations of its inventor.

#### A STEAM HEATED IRONING MACHINE.

The machine herewith illustrated is designed to facilitate the ironing of towels, napkins, table cloths, and other goods. It has two steam heated cylinders partly



CORBETT'S IRONING MACHINE.

inclosed in a sheet iron drum, in which are two doors, by the opening or closing of which the goods are made to pass out at the rear of the machine or are returned to the front, as the operator desires. In ironing collars, cuffs, and similar articles, which may require to be passed several times through the machine, one of these doors is closed, so that the goods passed through on that side are returned to the front until the work is sufficiently ironed, when the articles are finally passed through on the other side and delivered through the other open door on the rear side of the machine. The



## THE PREMIUM FOLDING STOOL AND CHAIR.

The object of this improved form of chair is to permit a greater spread of the legs, which renders it more steady and more firm on its foundation, and also enables it to be packed into a small space for storage or transportation. It will be noticed that the slant of the back rest and of the legs is not the same, and to provide for these different slants, the back rest and legs are made in separate pieces. It is not possible to construct the back and legs of one continuous straight piece and accomplish this. If the legs were continued



straight up to form the back, the inclination would be too great, while if the back is raised to a comfortable angle the legs would be too close together, rendering the chair uncomfortable and unsteady. This objection is sometimes overcome by curving the back and legs to an angle, but this prevents the chair from being folded into a very compact form. Since


the back is independent of the slant of the forward legs, it may be adjusted to any angle desired, by simply changing the point of its pivoted connection. When folded, the chair occupies only about one inch and a half in thickness, and a space of 60 ft. will hold enough chairs for 500 people, or chairs of this design can be placed in a hall or opera house for seating 2,000 people, and yet may be stowed away under the stairs or beneath the side benches.

A very desirable feature of this chair is that the back section is made detachable, and the chair may thus be readily converted into a neat camp stool.


This chair is the property of Mr. Hiram F. Henry, of Gowanda, N. Y.

## A PEN FOR DOUBLE AND SINGLE LINE RULING.

A ruling pen, consisting of two pens combined in convenient form for use, one of the pens capable of making two lines at a time and the other a single pen, is shown in the accompanying illustration, and forms the subject of a patent recently granted to Mr. Christian A. F. Orlob, of Salt Lake City, Utah Territory. The pens have each a square shank which fits into a corresponding aperture in a cross piece secured to the handle, and to use either pen singly one has only to turn the other in its socket at right angles to the normal position, or it can be readily removed from the socket. The center plate of the double pen is split into two prongs at the point, and the distance of the side plates therefrom is regulated in the usual way by the small nuts, according to the thickness of the line to be made, the pen, when filled with ink, making a double line without permitting the ink to run from one pen to the other. The other pen is such as used for ordinary ruling, but it has a joint to permit of swinging the lower end of the pen toward or from the double pen, decreasing or increasing the distance between the double line and the single line.



ORLOB'S RULING PEN.



BARROWS' FURNITURE ATTACHMENT.

## A New Repeater.

According to the semi-official *Berlingske Tidende*, the new repeating rifle of Captain Wadsen and Lieutenant Rasmussen is to be introduced in the Danish army. In this rifle the barrel is not fixed to the stock, but is secured by a spring. In firing, the barrel is forced backward, by which motion the bottom plate of the breech is opened, the empty cartridge ejected, and a fresh cartridge pushed forward into its place, the magazine holding six cartridges. The bottom plate is then closed again, and all these movements are made automatically, so that the rifle need not be taken from the shoulder. All that is required to be done is that, as soon as the six shots are fired, the magazine is refilled. The rapidity of firing is stated to be marvelously rapid, as many as six shots having been fired in a second (?) In aiming, of course, more time is required; but if the aim is once taken, the six shots may be fired in succession.—*Broad Arrow*.

## Gold on Alaska Islands.

Samples of ore from a new mining discovery in Alaska are on exhibition at the office of Geo. W. Sessions, in Nevada Block. The new mines are on Ounga Island, one of the Choumagin group, 100 miles west of Sitka, 200 miles east of Ounaska, and 1,200 miles north of San Francisco. The island is near the southwestern shore of the Alaskan peninsula. It is about 14 miles long and 6 wide. Geo. C. King, who went there for the Sitka Mining and Commercial Company last summer to look for coal and copper, found the ledge in September. In December another expedition of the same company went up and made more careful investigation. The result was that early in April another expedition, with a number of miners, a five stamp mill, and supplies, landed on the island.

Active work was begun on the ledge. It has been traced for some 10,000 feet. It was found that the porphyry hanging wall on the east was 200 feet from the outcrop, the granite foot wall on the west was 800 feet from the outcrop, and the outcrop was at no point less than 100 feet in width.

To determine the value of the rock in the ledge, two crosscuts were started—one from the east side and one from the west—at a vertical depth of 50 feet. The crosscut from the west, at a distance of 20 feet, struck a body of galena ore, which was from 2 to 4 feet thick in the bottom of the cut, the day before Mr. Sessions left for home. The assays were from \$5 to \$200 in gold and silver, and the ore also carried from 70 to 80 per cent galena, which alone, at present quotations, is worth \$90 per ton.

It will be remembered that the big mine of Alaska, known as the Treadwell, is on an island—Douglass—and there are plenty more islands to prospect. This new discovery will doubtless cause a more vigorous prospecting on the islands as well as mainland of Alaska. A mining district has been formed on Ounga Island, where the big ledge has been discovered.—*Min. and Sci. Press*.

## A DUSTLESS CARPET SWEEPER.


The invention herewith illustrated, which has been patented by Mr. John M. McClain, of Catlin, Col., consists of a fan wheel rotated in a sweeping box and a moistened dust catching wheel emptying into a water trough. The sweeping box has low runners on the sides, on which the device is pushed forward over the floor, and on its front is a vertically adjustable brush, one edge being provided with wire and the other with hair and jute bristles, the brush being reversible at will. As the device is pushed forward, a fan wheel in the front compartment is revolved by turning the crank, when a current of air is caused in the direction shown by the arrows, catching the dust raised by the brush and carrying it back over a dust pan and upward against a dust wheel. This dust wheel, which is set in motion by the current of air, just dips its rim in a water trough in the bottom, thus keeping it moist, and at the same time deposits the collected dust there, the heavier particles not thus carried up on the dust wheel being deposited upon the dust pan, which is situated between the water trough and the open bottom part of the sweeping box in front.

## A WALL PROTECTING ATTACHMENT FOR FURNITURE.

To preserve walls from being broken and furniture from being marred or scratched, Mr. Frederick Barrows, of Haverhill, Mass., has devised and patented an attachment, such as shown in the accompanying illustration. It consists of a roller of wood, rubber, or other suitable material, mounted to turn loosely on its axle, the latter being held in the upper and lower ends of a bowed supporting arm, which is pivoted between lugs upon a bracket secured to the back of the sofa or other article of furniture. A plate spring is also employed to exert a slight outward pressure against the back of the bowed supporting arm below its pivot. It is intended that two of these rollers shall be attached to the back of a sofa, bedstead, or other large article of furniture, while one will be sufficient for chairs and similar small pieces.

## AN IMPROVED KEY HOLE GUIDE AND ESCUTCHEON.

The practice of cutting a slot in the wood, where a mortise lock is used, to guide the key to the key hole, and covering this slot with the ordinary key hole escutcheon, is often carried out in so unworkmanlike a way as to make it difficult to insert the key in the lock. The register of the slot with the aperture in the lock is generally only approximate, and it is usually roughly cut and a good deal too large. To overcome





PATTERSON'S KEY HOLE GUIDE AND ESCUTCHEON.

this difficulty, Mr. Samuel S. Patterson, of 233 South Street, Wilkesbarre, Pa., has patented the combined key hole guide and escutcheon shown in the accompanying illustration. A circular recess is cut in the framing over and leading to the key hole, and therein is fitted a cylindrical boss, formed integrally with the escutcheon, but having a key hole slot which continues and exactly registers with that in the escutcheon, and also registers with the key hole of the lock. The escutcheon may be secured to the framing by screws in the usual way.

## AN IMPROVED WATER GAUGE FLOAT.

The accompanying illustration represents a glass water gauge attached to a boiler, and within the gauge a float of novel design, which has recently been patented by Mr. Loudon Campbell, of Alexandria, Va. The float is made of dark blue glass, highly tempered to prevent its breaking, and is provided near each end with encircling rings forming projecting flanges. These rings serve as scrapers within the tube of the water gauge, during periods of ebullition and under the normal action of the boiler, scraping the froth and scum from the inner surface of the tube, and keeping it always in a bright and cleanly condition. The float thus indicates the height of water in the boiler in so plain a manner that it cannot fail to be observed by a casual glance, while it can be easily seen from a considerable distance. A spiral spring, not shown in the illustration, is placed in each end of the gauge tube to prevent breakage of the float when the tube is blown out and the float goes to the bottom.

This improvement is applicable to all classes of steam boilers, being especially desirable in gauges where the water used is muddy or impure. It is now being used by steamers on the Potomac River and by several manufacturing concerns.



McCLAIN'S CARPET SWEEPER.



#### Death of a Notable Elephant.

Bijou, the great pet elephant who has for two years been on exhibition in the World's Museum on Washington Street, Boston, and previously was a resident of the Central Park menagerie in New York, is dead. This animal is the oldest and had been in captivity longer than any elephant ever on exhibition. Bijou has been in this country for sixty years, and while he is known to be seventy-five years old, the probabilities are that he was born nearly a hundred years ago. Recently he had suffered greatly from old age, and his efforts to stand up and receive cakes and candies from visitors at the museum, as he used to, were painful in the extreme. In the last two weeks his massive legs refused to support the weight of his huge body, and his attempts to respond to the call of his old trainer were very affecting. He would try to raise himself on his knees, and then reaching his trunk toward his keeper, the huge beast would settle back and moan.

The old elephant had also lost his appetite and was growing thin. He found it hard to sleep, and lay awake nights groaning and in such evident pain that it was decided to kill him. A box of chocolate drops saturated with a powerful poison was given Bijou after the museum closed on the night of June 19, and in forty-five minutes the beast twined his trunk affectionately around his keeper and died. Bijou's body will be buried in an underground air tight vat until decomposition is complete. This will require some nine months, after which the bones will be separated, bleached, and then prepared, and in another month the skeleton will be placed on exhibition at the World's Museum.

Bijou was an African elephant. Sixty years ago he came to this country, since which time he had traveled with nearly every circus on the road. Twenty times, it is said, his ownership changed hands, and with each stranded show poor Bijou would get a new master. When a youngster he was owned by a London tavern keeper, who exhibited him with a pair of immense gorillas in his tavern, and from there he drifted across the Continent. When but an infant, Prince Albert of England rode him and made him a pet, but his after life was not so pleasant.

In 1840 he visited Germany with a prominent showman, and tramped back and forth throughout the world until 1873 and 1874, when he was an attraction in the Great Eastern Circus. Then O. P. Older, a well known circus man, purchased him, and later Bob Frier, an equestrian with Barnum's circus, broke him to tricks.

Bijou then went to California, and at last drifted back to New York. On the way home, in crossing a bridge Bijou refused, after trying the planking, to make the passage. His keepers, it is claimed, goaded him on. He took a few more steps and plunged through the rotten boards, spraining his ankle, and since then he has never been himself.

While in the Central Park menagerie in New York, the agent of the World's Museum bought him. That was two years ago, and until within three weeks Bijou was never off his feet, even to lie down. He was considered one of the best trick elephants in the country. He played five tunes on the harp, played the harmonica, stood on his head, and did the housekeeping business for the circus with all the intelligence of his nature. During his sickness he has been fed largely on fruit, and a day's allowance included two dozen oranges, twelve loaves of bread, one hundred and fifty pounds of hay, half a bushel of grain, and a bucket of shorts.

Bijou was valued at \$3,000, and was probably better known throughout this country than any elephant ever on exhibition.—*New York World*.

#### Test for Animal and Vegetable Fibers.

A new method has been enunciated by Hans Molisch, in *Dingler's Polytechnisches Journal* (No. 261, 135), for distinguishing between animal and vegetable fibers, depending on two new sugar reactions.  $\alpha$ -naphthol and thymol give characteristic reactions with cane and grape sugar, which are more delicate than the tests of Trouner and Fehling in common use. The method of procedure is as follows: 5 cub. cm. of the sugar solution are mixed with one or two drops of a 20 per cent solution of  $\alpha$ -naphthol in alcohol, and then concentrated sulphuric acid is added in large excess. A deep violet coloration is produced, which gives rise to a bluish violet precipitate on dilution with water. Thymol similarly gives a red brown precipitate. Glucosides and carbo-hydrates, after treatment with sulphuric acid, will also respond to these tests, so that the celluloses in the cell walls of plants may be detected by its use. As animal fibers do not contain any sugar or carbo-hydrates which are capable of giving this color reaction, they can be readily distinguished from plant fibers.

Satisfactory results have been obtained with linen, cotton, hemp, jute, China grass, straw, and many other substances of vegetable origin; while wool, hair, etc., give no reaction. With silk, however, a transient color is produced, especially if the boiling has been continued for some time. When wool is to be tested, it is neces-

sary that it should be first well cleansed, as "wool lice," a feature of vegetable origin, gives the color reaction. Also, many fabrics made from animal fibers are finished with gum or mucilage, which must be removed before the test is applied. Any coloring matter present, according to the author, does not prevent the reaction from being seen.

#### A NEW STYLE OF THERMOMETER.

In the *SCIENTIFIC AMERICAN* for December 5, 1885, we published an interesting letter from Dr. Warren, of Boston, Mass., in which he described at considerable length the disadvantages of the common thermometer and the urgent need there was of a new form of instrument, especially for medical purposes. Since that date there has been brought into market a new and ingenious form of thermometer, Immisch's avitrous thermometer, which seems to answer many, if not all, the requirements. We give an engraving of its exterior



appearance and size, the cut being the same size as the article itself. The interior mechanism consists of a small tube, bent in circular form, having one of its ends fixed to a support, the other end free to move, but connected by a fine spring with a shaft carrying the indicating or dial pointer. The tube is filled with a highly expansible liquid. Any variation of temperature causes the tube either to curl or expand, as the case may be, and thus moves the pointer. There is a stop catch, by which the pointer may be held or locked to show its indication as long as desired.

The instrument is waterproof and durable, very sensitive to slight changes of temperature, and very accurate. This fact is established by the guarantee of the Kew Observatory, which accompanies each instrument. Altogether, this is a scientific and desirable form of thermometer, which every medical man especially should be provided with. Messrs. Sardy, Coles & Co., 96 Maiden Lane, New York, supply the instruments and give further information.

#### LARVÆ OF BOT FLY IN HORSE'S STOMACH.

BY JAMES F. McDUGALL.

I have lately had sent to me, by the son of one of our most eminent breeders, a portion of a horse's stomach, containing a great number of large maggots (the larval form of the horse bot fly) adhering in thick clusters to the lining of the stomach. The gentleman in forwarding specimen writes me that the number of maggots in the entire stomach would have filled a peck measure. I am strongly of opinion that these maggots are much more prevalent in horses' stomachs than has hitherto been made plain.

I have spoken to a number of veterinary surgeons with large country practices, and they inform me it is quite a common thing with horses that have died between January and June to find these maggots in large numbers in the stomach, especially if the animals were at pasture the previous summer or autumn.

The maggots are produced from eggs laid by the horse bot fly (*Gastrophilus equi*). The female deposits her eggs upon those places which are most easily reached by the animal's tongue, as, for instance, the



HORSE BOT FLY MAGGOTS ON LINING OF STOMACH.

shoulders, the legs, the inside of the knees, etc. The effect of the moisture and heat of the tongue seems to be such that licking the places where the eggs have been deposited liberates the minute maggots contained in the eggs, which adhere sufficiently to the tongue to be carried from thence with the food into the stomach. On reaching the stomach they immediately attach themselves to the lining by means of two small hooks with which their mouths are furnished. Here they remain till the following spring, feeding upon the mucus secreted by the mucous membrane. When full grown, they are about an inch in length. When the maggots are fully developed from the larvæ, they are removed from the stomach during ordinary evacuations.—*The Farmers' Gazette, Dublin, Ireland*.

#### Many Items of Interest.

At a recent meeting of the Polytechnic Society of Berlin, says the *Journal of the Telegraph*, the question was asked, What studies are best to fit one to be an electrical engineer? Herr Frischen, one of Siemens and Halske's experts, replied that much practical experience was required. After graduating from school, a rigid course in an advanced technical school should be taken, followed by an apprenticeship in a factory. He remarked that at present the title of electrician is used too freely, and that the claim of some to it is that they have nailed up a few wires.

A lens which magnifies, and yet is perfectly flat on both sides, is a scientific novelty. It is made at Jena, by the manufacturer of Professor Abbe's new optical glass. The lens consists of a single disk, whose density varies so that its refractive power decreases regularly from the surface inward.

To purify water in glass vessels and aquariums, it is recommended to add to every 100 grammes of water 4 drops of a solution of 1 gramme of salicylic acid in 300 grammes of water. The *Norsk Fiskeritidende*, published at Bergen, Norway, says that thereby the water may be kept fresh for three months without being renewed.

An observer down South says an alligator's throat is an animated sewer. Everything which lodges in his open mouth goes down. He is a lazy dog, and instead of hunting for something to eat, he lets his victuals hunt for him. That is, he lies with his great mouth open, apparently dead, like the possum. Soon a bug crawls into it, then a fly, then several gnats, and a colony of mosquitoes. The alligator doesn't close his mouth yet. He is waiting for a whole drove of things. He does his eating by wholesale. A little later a lizard will cool himself under the shade of the upper jaw. Then a few frogs will hop up to catch the mosquitoes. Then more mosquitoes and gnats will light on the frogs. Finally a whole village of insects and reptiles settle down for an afternoon picnic. Then all at once there is an earthquake. The big jaw falls, the alligator blinks one eye, gulps down the entire menagerie, and opens his great front door again for more visitors.

The application of soda ash or any other scale solvent to a dirty boiler, the editor of the *Locomotives* says, should be followed by a thorough cleaning shortly afterward to remove any scale which may be detached or loosened, or injury to the boiler may result. The idea obtains in some cases that it is only necessary to put the solvent into the boiler and let it work, no further attention being necessary. This is a great mistake. If a solvent does any good, its action is either to loosen scale so that it becomes detached in flakes, or it dissolves it so that it remains in the water, either in a finely divided state or in solution. In the first case, the accumulation of a mass of scale on the bottom of the shell is more than likely to result in burning the plates. The only thing to do is to open the boiler and remove it mechanically.

In the second case the result will depend more or less upon the nature of the scale and the amount and character of impurities that find their way into the boiler. If the scale is cut by the action of the solvent into a fine powder, and grease gets into the boiler, as it will in all cases where an engine exhausts into an open heater for the purpose of heating the feed, trouble is sure to result. Burned plates may always be expected under these circumstances. The only thing to do is to blow off all the water in the boiler, thoroughly clean it out, and begin again, omitting the grease.

Gold will only melt at a comparatively high temperature, as we all know, but what is not generally known, the *Jewelers' Journal* says, is that if two per cent of silica be added to the gold, it can be melted over the flame of a common candle.

From the same source the reader may learn that a pretty alloy, said to resemble gold exactly, can be made with 16 parts copper, 1 of zinc, and 7 of platinum. The copper and platinum are covered first with borax and then with powdered charcoal and melted, then the zinc added, and the alloy thus produced is exceedingly malleable, and can be drawn into the finest wire, while it never tarnishes.

#### Food Adulterations.

The examinations as to tea, coffee, and sugar conducted by Edward G. Love, Ph.D., for the *New York World*, resulted as follows:

A review of the 300 reports discloses that of the samples of tea, 88 were not adulterated and 12 were adulterated, mostly with "lie tea" and foreign leaves; that of the samples of ground coffee, 72 were unadulterated and 28 were adulterated, mostly with chicory and peas; that of the sugar samples, 98 were pure and only 2 adulterated with starch glucose. In all, there were, of the 300 samples, 258 good and 42 more or less bad. As to the weights of the samples, those of 270 were correct and 30 were light.



**Resin in Soaps and Fats.**

According to the authors, the methods of Sutherland, Gottlieb, and Heiner do not give quantitatively useful results. They recommend a modification of Gladding's process. From 1 to 3 grms. soap are dissolved with heat in 80 per cent alcohol, the solution, if acid, is neutralized with ammonia, mixed with excess of a 10 per cent alcoholic solution of calcium nitrate, and filtered when cold. The filtrate passes through at first turbid, and must be repeatedly poured back. The precipitate is washed several times with 80 per cent alcohol, mixed in a roomy flask with an excess of silver nitrate solution, and diluted with three volumes of water. After some shaking, the precipitate (if a sufficiency of silver solution has been used) collects on the surface, and the solution is nearly clear. It is filtered, and the precipitate is washed with cold water until the washings no longer give a precipitate with hydrochloric acid. The washed precipitate is dried at 70° to 80°, and washed with ether into the same flask in which was the silver precipitate, and which must have been dried internally in the mean time.

After some time the ethereal solution is filtered through a dry filter into a graduated 100 c. c. cylinder, and the undissolved portion is washed with ether until the filtrate makes up 90 c. c. The ether which flows through last must be colorless. If 90 c. c. do not suffice, a larger graduated cylinder of about 250 c. c. may be used. The solution is then mixed with about 10 c. c. of dilute hydrochloric acid, well shaken for a long time. The cylinder is then filled with ether or hydrochloric acid up to the mark and shaken again. If the operation has been well managed, the precipitate of silver chloride settles quickly, and the ethereal solution of the resin is quite pure and transparent. The volume is read off, from 50 to 60 c. c. are taken with a pipette, the ether is distilled off, the residue dried at 100°, and the resin weighed. From the weight we must deduct 1.6 mg. for every 10 c. c. of the ethereal solution, on account of oleic acid which has been dissolved.—A. Grütner and J. Szilasi, *Chemiker Zeitung*.

**A Steam Engine of 1809.**

Retained in perfect running order in the United States Steamboat Inspector's office at Louisville, Ky., says the *Louisville Courier Journal*, is an oscillating engine constructed in 1809 by Daniel French. It is only of model size, and is probably the first engine of the kind ever constructed. Its description is simple. Having its piston rod attached directly to the crank pin, as the crank revolves, the cylinder oscillates upon trunnions, one on each side of it, through which the steam enters and leaves the steam chest. The valves are within the steam chest, oscillating with the cylinder. It is perhaps as satisfactory an engine of this class as has ever been built, for it is well known that the mechanism actuating the valves in oscillating steam engines has seldom proved perfectly satisfactory in its operation.

The inventor, whose son carried on a shipyard for years at Jeffersonville and was well known to many of the older citizens of the city, was contemporaneous with Robert Fulton, who built a steamboat on the Seine in 1803 with Chancellor Livingston, and who, in 1806, with Livingston, had a boat built on the Hudson, in which he placed machinery claimed to have been made by Boulton & Watt in England.

Daniel French had litigation with Fulton about this steamboat, claiming that the latter had appropriated his invention, but Fulton was backed by Livingston's influence and capital; and, though the case was before the courts for many years in one form and another, French was finally defeated. Although the oscillating engine on exhibition in the steamboat inspector's office was not built till 1809, it was by no means the first attempt French had made to invent an engine applicable for steam navigation. He had been known as an inventor for a quarter of a century before, and his numerous inventions of different kinds had given him an extensive and esteemed reputation. Those who knew him were wont to say that he was half a century ahead of the time in which he lived.

It is not improbable that Fulton was familiar with French's experiments with steam. It is an historical fact that in connection with his profession as an engineer he had passed years in the scientific experiments the result of which forever identified his name with steamboat navigation. It is not to be doubted, therefore, that he was acquainted with the efforts of every experimenter of the power of steam in this direction, from the time that Blanco de Garay is supposed to have actually applied steam to the propulsion of a ship at Barcelona, in the year 1543, up to the time when, in 1763, William Henry, of Chester County, Pennsylvania, tried his model steamboat on the Conestoga river. Fulton witnessed that experiment, and it is a matter of record that he was familiar with the work of the numerous contemporary inventors in America, and had visited England, where he found others at work on the same problem. But with this invention, as with all others, though the claimants may be numerous, the credit attaches to the one most successful in bringing it before the public.

**Roburite, the New Explosive.**

A most important and interesting series of experiments was lately carried out at the School of Military Engineering, Chatham, England, under the superintendence of Major Sale, R.E., and in presence of Lieutenant-General Sir John Stokes, K.C.B., R.E., Admiral Colomb, Major Cundill, R.A., Her Majesty's Inspector of Explosives, and a large gathering of other officers and gentlemen.

The new German explosive, roburite, belongs to what is known as the Sprengel class or type, being a mixture of two substances, neither of which separately possesses explosive properties. In this case both components are solid, and the resulting mixture has a sandy, granular appearance, somewhat resembling the commonest yellow sugar. Roburite is the invention of Dr. Carl Roth, an eminent German chemist and analyst, who claims for it the following advantages over other explosives:

1. That the two components are perfectly harmless and inert separately, so that they can be stored and transported without any restriction whatever.
2. That even when mixed or ground up together in an ordinary coffee, cement, or flour mill, the mixture is perfectly safe to handle and use, as neither percussion, friction, nor the application of an ignited or heated body will cause it to explode. This can only be effected by using a detonator charged with fulminate of mercury.

3. That, when detonated, roburite produces neither spark nor flame, and will not, therefore, ignite firedamp nor coal dust in mines. Dr. Roth states that this point was decided by the trials of the Imperial German Commission upon Accidents in Mines, and that, in consequence, this explosive is now being introduced into the coal mining regions of Germany, as affording absolute safety to the men employed.

4. The amount of noxious gases produced by its explosion is so infinitesimal, that for this reason alone it is superior to other explosives in common use for longitudinal and deep mining work. The report from a mine in Westphalia, with shafts about 1,500 ft. deep, states with reference to roburite: "The men are not inconvenienced by the gases, and experience no difficulty whatever in breathing the moment after a shot has been fired, and they resume their labor at once."

5. Roburite is not subject to deterioration through climatic variations of temperature. It should be kept dry, but if it becomes damp, its strength can be safely restored by drying.

The object of the trials was to test roburite in comparison with gun cotton, dynamite, and blasting gelatine. The programme of the experiments actually carried out was as follows:

**A. Safety Tests.**—After being ground through a small hand mill, the substance was struck direct and glancing blows with heavy hammers upon iron plates, without any result. Flame was then applied to a portion of it by means of a short length of Bickford fuse, but without igniting the mass. Thrusting a red hot iron from a portable forge into the roburite caused only slow combustion and crepitation locally, which ceased when the iron was withdrawn. When a quantity was put on the forge fire, it merely burnt away like an ordinary combustible. Dr. Roth wished to fire a powder charge in contact with the roburite, but it was considered that the above named tests were more severe.

**B. Test on Mild Steel Plates,** 2 ft. 6 in. by 2 ft. 6 in., and of various thickness.—These plates were supplied by the Patent Shaft and Axletree Company, Limited, and were laid flat in shallow trenches, a hollow being left underneath the central portion of each plate; heavy timber balks were stacked around each square trench, with the object of showing the comparative dispersive force of each explosive.

**I.** Three pounds each of dynamite and roburite were placed on the center of plates 2 in. thick, some sandy loam being piled loosely on top. The results of detonation were that the dynamite produced a dent in center of plate 1½ in. deep; the indentation produced by the roburite was about 1½ in. deep, but the bulge appeared to have a wider area than in the former case.

**II.** Five pounds each of roburite and gun cotton were then exploded upon the same plates, with the result that in the former case the plate was smashed into four tolerably equal pieces, while the gun cotton made a breach through the center of the plate somewhat resembling that which would be caused by the penetration of a large projectile. The diameter of the hole was roughly 12 in., with five radial fissures almost reaching the edges, the longest 15 in., the plate being at the same time bent into the shape of a pack saddle. This would seem to have been a remarkably tough piece of metal. The timber balks were scattered in all directions.

**III.** Eight pounds each of dynamite and roburite were then detonated upon plates 3 in. thick. The dynamite caused an indentation 2¼ in. in maximum depth, while the roburite gave a bulge 3 in. deep in the center, and of a larger area, reaching apparently almost to the corners of the plate.

**IV.** This series of tests was concluded by exploding 12 lb. each of roburite and gun cotton on plates 4 in.

thick, rather more loam being heaped on top of each. The roburite caused a wide indentation 1½ in. deep in center, while the tremendous local force of the gun cotton was exemplified in a striking manner. In addition to an indentation 3½ in. in greatest depth, a small crack appeared to extend right through the plate, this crack corresponding with one edge of the lowest slab of gun cotton, the rectangular shape of which could be clearly seen indented on the steel plate, the depth being ¼ in. at the crack and ¼ in. along the other edges of the slab. There is a circular hole drilled in the slab of wet gun cotton to receive a small cylindrical disk of dry gun cotton, as a primer, and the position of this disk was marked by a circular hollow in the steel plate ½ in. deep in center.

**C. Blasting or Mining Test in Brickwork.**—Three holes, each 1½ in. in diameter and 18 in. in horizontal depth, were drilled in the solid brickwork of the counter-scarp wall, and were respectively charged with 2 oz. of gun cotton, blasting gelatine, and roburite. The holes were then tamped with loam in the ordinary manner, and fired by means of short lengths of Bickford fuse. The gun cotton produced no apparent effect upon the brickwork, but Major Sale was of opinion that the hole must have been open or very weak at the back. The blasting gelatine produced violent local action, displacing the brick through which the hole had been bored and the four adjacent to it. There was a slight bulge in the wall, the cracks extending radially from 10 in. to 12 in. The roburite exhibited a more widespread rending action upon the wall, the radius of disturbance being 15 in. or more, and the bulge being also greater. Rather larger charges of each explosive would have afforded a more satisfactory comparison.

**D. Ground Mines.**—Ten pounds each of gun cotton, blasting gelatine, and roburite were loaded into holes in the bottom of the ditch 4 ft. deep by 8 in. in diameter, filled up with sand, and slightly tamped. The explosion of these charges cast up tremendous fountains of loam and sand, and resulted in the following craters: Gun cotton, 10 ft. 6 in. wide by 1 ft. 8½ in. deep; gelatine, 14 ft. 6 in. wide by 3 ft. 7 in. deep; roburite, 12 ft. 3 in. wide by 2 ft. 9 in. deep. The explosion of the gun cotton mine appeared to cause great local action, but it will be seen that the area and depth of its crater was considerably less than that caused by the roburite, which again must yield the palm, in this instance, to the blasting gelatine. It is, however, to be remarked that these mines had been placed much too close to one another, so that their craters crossed; this would give whichever charge was the last to explode a certain advantage.

In summing up the results of the foregoing experiments, we must bear in mind the great difficulty—we had almost said the impossibility—of obtaining any absolute standard of comparison of the relative strengths of two or more explosives. Each will seem to prove itself superior for certain purposes. Judged, however, by any standard of comparison, it appears that the new explosive has acquitted itself very well, and—especially when we consider its absolute safety—must have a great future before it. Roburite has shown itself to be in some respects more powerful than dynamite, to which it is likely to prove a serious rival in the industrial field, although the latter has the proverbial advantage of strong possession of the ground. An important element in the struggle for ascendancy will be the price at which roburite can be supplied, as compared with dynamite, and this will be, we understand, strongly in favor of the new substance.

As regards the military application of explosives, there is nothing in the results of these trials to disturb the firm conviction of our government that gun cotton is the best adapted for torpedo charges, submarine mining, and hasty demolitions of all kinds. Its superiority in local force to dynamite, when employed without any confinement, is once more strikingly demonstrated, to say nothing of the far greater safety of wet cotton, and its applicability for use under water with no other confinement than that of a net to keep the slabs together. But although quite outside the scope of recent experiments, the great power and perfect safety of roburite seem eminently to fit it for use as a bursting charge for shells, into which its granular form would allow it to be conveniently loaded. Much stronger than any picric powder, and doubtless better able to withstand the concussion of the discharge of the gun, an extended series of trials would be necessary to determine the best mode of so employing it.—*Engineering*.

**Coppered Tin.**

Mr. P. H. Laufmann, Pittsburg, is manufacturing copper-plated sheet steel, which indicates a new use for that metal. The sheet is made of decarbonized steel, and is manufactured at the Apollo Sheet Iron Mills. After being rolled to the proper thickness, it is electroplated with copper on both sides and tinned on one side, and in this condition, it is stated by the manufacturers, it is a better article for many purposes than solid sheet copper.



## NEW FRENCH ARMORCLAD CRUISER LE TERRIBLE.

It appears that the fleet of armorclads, which not long since appeared to have grown senile in the presence of the more modern torpedo boat, is now more in favor than ever with the navy men. All the great nations are taking every step to increase the efficiency of their navies, both in constructing ships of enormous tonnage and in constructing new types of ships. Without leaving out of sight the necessity for a fleet of torpedo boats, France ought to follow this movement. The maneuvers of last year have not dethroned the ironclad. Those of this year, we are ready to affirm, will not lessen the prestige of those magnificent ships which are the honor of our navy. Let us rejoice at this most recent addition to the fleet of a new type of cruiser.

The Terrible, which was launched in 1881, satisfactorily finished its trial test during the latter part of the winter. It is now entirely finished. This ship is a mate of the Requin, which was constructed in the shipyard of the Loire, and which was launched in 1885.

The hull is of iron and steel, and measures 280 ft. in

art, and to that portion of his invention which does not include any portion of public knowledge, or the work of other inventors, whether patented or not in any country, and that the time covered by this investigation covers the early period of their history before the system was thoroughly formulated and crystallized by legal decisions, this is a remarkable showing, testifying to the skill of the patent solicitors, and also the examiners in their patent department.

It is difficult to estimate the value of the patents still in force. Although such estimates have been made, they are necessarily vague and void of the precision essential to accurate statistics; yet the amount of capital invested in faith upon the validity of patent protection is very large, and generally remunerative to a satisfactory degree.—*Engineering*.


## The Exhaustion of Petroleum.

A writer in *Home Knowledge* discusses the problem of the exhaustion of our oil fields in the following manner:

It can hardly be doubted, I fear, that the supply

nearly exhausted. In less than a generation a small part of the population of this continent alone has used up nearly all the valuable stores of energy which had been accumulated during millions of years of the geologic past.

More recent inquiries confirm the conclusions of Professor Lesley and Mr. Carll. The signs of exhaustion in the oil-producing regions can now be clearly recognized. During the last four years there has been a steady diminution in the output, accompanied by an increase in the price per barrel, which nevertheless does not even maintain the nominal annual value of the supply. Mr. Wrigley announced in 1882 that 154,000,000 barrels of oil had already been raised up to the beginning of that year, and expressed the opinion that not more than 96,000,000 barrels remained to be raised. In this last estimate he was undoubtedly mistaken, for up to the beginning of 1885 no fewer than 261,320,300 barrels had been raised, and in the year 1885 as many as 21,042,041 barrels (nearly 3,000,000 fewer than in 1884) were obtained. But although the estimate of 1885 of the quantity of oil still remaining fell far short of the



THE NEW FRENCH ARMORED WAR SHIP TERRIBLE—7,200 TONS DISPLACEMENT.

length, 59 ft. beam, with a draught of 23 ft. 9 in., 7,168 tons displacement, with armor plating 50 centimeters in thickness amidships, 37 centimeters forward, and 33 centimeters aft. It is provided with 12 boilers.

The armament, mounted on the fore-castle, consists of two cannons of 47 centimeters, four cannons of 10 centimeters, and ten machine guns. There is a complement of 332 men.—*L'Illustration*.

## Stability of Patents.

Although the patent system of the United States involves a search on the part of the government as to the novelty of the invention, yet it has been a frequent remark on the part of the general public that few patents can stand the tests of the courts. This ratio is sometimes stated to be as high as nine out of ten, or some equally conventional fraction. A member of the bar has recently tabulated the adjudication of patents by the United States courts, as recorded in Meyer's Federal Decisions from 1776 to 1885, and finds that 73 per cent of the patents upon which suit was brought were sustained. The total number of patents brought to an issue was 983, and of these 269 were annulled, and of the remaining 714 which were held valid, 490 were sustained in full, and 224 were held to be valid in part. When it is considered that the United States patent law requires that protection can be accorded only to the original inventor who has added to the state of the

both of oil and gas has now been so largely drawn upon that within less than a score of years scarcely any will be left which can be brought at reasonable cost into the market. The boundaries and extent of the oil regions have been determined. All the sands in which oil will ever be found in such quantities as to be worth working are known, and have been drilled through in various places. It is scarcely possible that any new fields will be discovered which will be comparable, either in extent or productiveness, with those now known. So far back as January, 1883, Professor Lesley pointed out that no petroleum is now being produced in the Devonian rocks, either by the process akin to distillation or otherwise. What has been stored up in the past, a process which probably lasted for millions of years, may be got out. But when these reservoirs are exhausted, there will be an end of the petroleum supply. "The discovery of a few more pools of 2,000,000 or 3,000,000 each can make little difference," Mr. Carll, whose opinion on the geology of the oil-bearing districts may be regarded as decisive, has come to a similar conclusion. "There are not at present," he pointed out quite recently, "any reasonable grounds for expecting the discovery of new fields which will add to the declining products of the old, so as to enable the output to keep pace with the shipments or consumption."

The stored petroleum in this region has then been very

truth, and though we may admit as possible that even now much more oil remains to be put out than the most experienced geologists suppose, the signs of approaching exhaustion are yearly becoming more unmistakable. The expense of bringing the oil to the surface grows greater year by year, and threatens soon to become so great that the profit of working the oil stores will be evanescent. So soon as that state of things is approached, we may be sure that the oilmen's occupation in Pennsylvania and western New York will be gone. It has been stated that the Japanese, unwilling to let the least fraction of the earth's interior stores be lost, have been known to excavate a vertical shaft to a depth of 600 feet in order to raise a few gallons of oil per day. But in America, when the oil mines are so near exhaustion as this, they will be abandoned; nay, they will be abandoned long before they approach such a condition. With the failure of the oil supply all the collateral branches of industry associated with it will fall, too.

THE green diarrhoea of infants is, according to Dr. Hayem, caused by a microbe which secretes the coloring matter characteristic of the complaint. The disease is epidemic and contagious. The best treatment, he said in his communication to the Academy of Medicine, is to give the child after each feeding a teaspoonful of 2 per cent lactic acid.



## RAISING A SUNKEN STEAMSHIP.

(Continued from first page.)

out as much of the cargo as the depth and other conditions admit, and then, if the hull is dangerously near the surface, blow it apart. The Merritt wrecking organization of this port, however, had such success in raising a sunken ship, the *Lornty*, in New York bay some time since, that the owners of the steamer determined to trust to them the work of raising the wreck. In spite of difficulties other than those interposed by nature, and which could scarcely have been foreseen, the steamer *Welles City* will in all probability soon be lifted intact from the bed of the river.

The work done by the wrecking company is as unique as it is interesting, and we will endeavor, by means of the clever drawings made by our artist, to describe its progress and the nature of the difficulties which from time to time appeared, though ineffectually, in the way of its accomplishment.

Fig. 3 is a picture of the steamer, and is from a photograph taken shortly after the steamer went down. As will be seen, she is half-brig rigged. Her topsail yards are cock-billed, showing that when she went down she had been made ready for docking. The




Fig. 1.—CROSS SECTION OF THE SUNKEN STEAMER, PONTOONS, AND SLINGS.

taut by the aid of fall-and-tackle and hydraulic jacks, and are then toggled on securely.

In the present instance, it was a difficult matter to get the chains under the ship, first because her hull was in some places sunk fully fourteen feet in the muddy bottom of the river, and again because of the unusual size of the chains required. If the reader will refer to Fig. 2, he will see a representation of the preliminary process of keel-hauling a sunken ship. The "sweep" chain, a light chain, has been dropped over the bow, and the diver is engaged in thrusting it under the fore-foot of the stem, so that it will run clear when pressure is put on from above to work it completely under the hull. This operation is called "sawing," and consists in working the chain from side to side until it forces its way through the sand and reaches that part of the hull where the first heavy or lifting chain is to be placed. The links of this sweep chain are only one-half inch in diameter.

Now the men attach a one inch messenger chain, and when the end has been pulled by the sweep chain completely around the hull and up to the surface on the opposite side, another and larger chain, and, perhaps, even another yet, takes the place of the first, until finally a big chain, with links  $2\frac{1}{4}$  inches in diameter and 14 inches long, is finally pulled completely




Fig. 2.—MODE OF PLACING THE SLINGING CHAINS.




Fig. 3.—VIEW OF THE STEAMER SOON AFTER THE ACCIDENT.

shrouds and stays are intact, and her smokestack shows its white band under the black—the insignia of the line to which she belongs. Here are her dimensions: Length, 275 feet; beam, 36 feet; depth, 23'6 feet; tonnage, 1,936 gross. The upper structure is of iron, and the hull of steel.

She was loaded with 25,000 boxes of tin and other cargo amounting to 1,900 tons, and before anything was done toward lifting her, this was removed by the aid of divers, as in the ordinary way.

In the old method of lifting a small vessel to the surface, ropes were made fast to the hull, fitted with a traveler, and then watertight casks forced down and made fast. Later on, this system was improved by sinking pontoons filled with water and carrying temporary weights; and when these were hooked on and the weights removed, the water was pumped out by means of hose connecting the pontoons with a steam pump affixed to the deck of the tender on the surface. This was an awkward, a costly, and, worse than all, an uncertain method, and utterly inadequate for the floating of a great ship like the *Welles City*. Captain Merritt's pontoons (see Fig. 1, A A) are of three sizes—100, 60, and 50 feet in length—and have apertures or wells isosceles triangle shaped (B B), which on deck are only large enough to admit heavy chains, but gradually enlarge toward the bottom, so as to admit of the play of the chains which descend through the pontoons which float on one side of a sunken vessel, and, passing under her hull, are carried up through the centers of the pontoons on the opposite side. These chains are hauled




Fig. 2.



Fig. 3.




Fig. 1.—IMPROVED AUTOMATIC CUT OFF ENGINE.

[FOR DESCRIPTION SEE PAGE 24.]

around the hull. This process is continued until a series of big chains are wrapped about the hull and brought up, as said before, through the openings in the center of the pontoons overhead.

The front page cut furnishes a good view of the sunken ship, with most of the large-sized lifting chains already set in position at stated intervals from stem to stern; the chains being closer together and most numerous immediately under that section of the hull which contains the boilers and engine. Immediately above, and on either hand, the big pontoons are floating; being kept apart, those on one side from those on the other, by stout cross beams, so that, when the ship is finally lifted, there will not be any impediment in the way of her reaching the surface. While some of the seventy men who comprise the wrecking crew are engaged in hauling and setting the chains, others lower away hogsheads filled with water into the open hatches of the sunken ship. When a score of these have been thus lowered, the process momentarily stops, and the diver at work down deep in the bowels of the hull makes them fast, and then attaches the end of a hose, let down from above, to the bung-hole of each in turn. The men on the deck of the wrecking schooner above apply the steam pump to the upper end of the hose, and the hogsheads, as they are emptied of their contents, have their plugs driven home by the submarine workman, who wields a heavy hammer fitted with a tapering driving end. These empty barrels, as may be imagined, add to the buoyancy of the hull and sensibly



lessen the lifting power required to raise the ship. And now we have the pontoons, the chains, and the tackle all ready, and only await the change from the ebb to the flood tide to begin bringing the sunken steamship to the surface. As soon as low water slack occurs, the river water is let into the great pontoons till their decks are fairly a-wash in the surface of the river. The slack of the chains is quickly gathered in, the fall-and-tackle, which, as may be seen in the frontispiece, depend from the tops of the standards on the pontoons, are called into action, the hydraulic jacks are worked, and the chains hauled taut. As the flood tide serves and the waters gradually rise, the great steam pumps are set to work and the water is pumped out of the pontoons, and it is now a question whether the weight of the sunken ship—2,000 tons—which keeps her below is greater than the inclination of the great submerged pontoons or air chambers to force their way to the surface with their burden. If not, then the hulk will leave the bottom of the river, and the whole mass—pontoons, tenders, and the depending wreck—guided by powerful tugs, follow the flood tide up stream. Referring to the hydrographic chart, a shoal spot is discovered in the river bed, and pretty soon the sunken ship is directed toward and grounded upon it, and, at the next low water, the pontoons are again flooded.

Once more they sink to their upper surfaces, once more the slack of the chains which support the hull is gathered in, and the water again pumped out of the pontoons. At the next flood tide, the pontoons show more and more of their sides above the surface, and the hulk again forsakes the river's bottom and is towed to another and still another shoal spot, the pontoons being flooded at low water and pumped out at high water till finally her decks are above the surface. Then the steam pumps are set to work upon her, and she is freed from water. Now the great, ugly pontoons and wrecking schooners that so ill become her are cast off, and once more the gallant ship is free for a further career of utility.

The difficulties which beset the way of wreckers engaged in such an enterprise as raising a great ship like this from the bottom of the river are many and continuous, and sufficient to deter even the most skillful were they not led by so courageous and resourceful a master as Captain Merritt. Little or nothing could be done save during slack water, say two hours during the twenty-four at most, and often not so much as this, because the spring tides this year, owing to the unusual rainfall, were very heavy, and consequently the low water slack has been so short in duration as to be at times scarcely perceptible; the great rush of waters down stream toward the estuary formed by the junction of the two rivers often overpowering the incoming flood from seaward until well along toward the end of the first quarter. The ebb has claimed the mastery for more than its allotted six hours; the effect being the backing up of the waters of the bay against the yet running ebb of the river. In this swash the wreckers had to work while the pontoons rolled from side to side in the contention of the waters.

At times, toward the middle of the ebb tide, when the swollen waters of the upper river got fairly under way, the current rushed by the point where the wreckers were at work, at a speed of quite four knots an hour; and one day, while the struggle for mastery between the ebb and flood tide was in progress, and the waters of the bay were backing up against the river's ebb, so severe was the wrenching of the great chains against the steel keel of the sunken steamer, caused by the bobbing about of the pontoons holding the ends above water on either side, that one of these great chains was cut in two. The writer saw the parted link. It was fourteen inches long by two and a half in diameter, and was almost bent double, being cut through the center as if by a knife.

At times, before the heavy chains were fairly made fast around the hull of the wreck, the wrecking colony were almost torn from their moorings by tugs coming down stream and stupid lightermen going up. On one of these occasions—it was on the early morning of March 27, before the cargo of tin had been taken out—two barges, the one loaded with brick, the other with plaster, drifted down upon them. The first scraped clear, while its mate ran foul of the protruding foremast of the sunken steamer, carried it away, and then went down, cargo and all, and settled itself athwart the fore hatch and fore-deck of the wreck. This had to be removed before the work could go on, because it was directly in the way of the sweep chains while passing under the bows of the sunken ship.

It is worthy of remark that the steamer *Lone Star* of the Morgan line, whose bow cut down the steamer *Welles City*, was destroyed by fire while lying at the cotton wharf on February 28.

#### The Photography of Projectiles.

A photographer at Peshth has succeeded in taking photographs of projectiles, fired from a Werendler gun, while having a velocity of 1,300 feet per second. The projectiles appeared on the impressions enveloped in a layer of air hyperbolic in form.

#### IMPROVED AUTOMATIC CUT OFF ENGINE.

The engine illustrated on the preceding page is manufactured by Messrs. McIntosh, Seymour & Co., of Auburn, N. Y. Great care has been taken that all the details should be in accordance with the best practice, and in design the engines are as compact and rigid, and as heavy in the stationary part, as could be desired. Those sections of the moving parts which usually show weakness have been made unusually heavy, although their gross weight has been carefully kept down. All the wearing surfaces are generous, and various devices for oiling them while the engine is running have been provided. Correctness, simplicity, and superiority of workmanship have been aimed at, while especial claim is laid to the efficiency of the balanced valve and the governor or automatic cut off regulator.

The valve is made very tight, has cast iron ends, and a tube connecting them. This is like the ordinary piston valve, and has been made in this form because it is very simple in form, is easy to make, and is perfectly balanced. In order to obviate the ordinary wear and tear from friction and the consequent loss of steam, an adjustable seat is provided, which consists simply of a crescent-shaped ring having steam ports through it which match with the ports in the steam chest itself. The ring is split, and is adjusted in place by a stem, which extends to the upper side of the steam chest, where it can be turned by a wrench. This construction enables the ring to be adjusted at any time a leak is discovered, and this may be accomplished quickly and easily. By using valves of large diameter and somewhat long travel, quick steam admission is secured and sharp cut-off.

The governor is located in the fly wheel, and consists mainly of a pair of weights pivoted at the periphery of the wheel and having inclined jaws, in which slide blocks, as shown in Fig. 3. These blocks turn freely in a pendulum, which is also pivoted near the periphery of the wheel (see right hand of governor in Fig. 2), and which is further connected with the eccentric and serves to either raise or lower the eccentric when it is subjected to a similar movement by the action of the sliding blocks in the jaws of the weights. As the speed of the engine increases, the weight will be lifted by centrifugal force against the action of the springs, and as they move outward the pendulum will be thrown over by the inclination of the jaws. This brings the center of the eccentric nearer the center of the shaft and shortens the travel of the valve, thereby reducing the cut off and, consequently, the supply of steam supplied to the cylinder.

The extreme change of speed from when the engine is running light to when it is working under its maximum load is very slight. In some experiments made to test this point the variation in speed when the load was changed from 1.1 h. p. to 33.8 h. p. was only one half a revolution.

#### How to Catch and Preserve Moths and Butterflies.

There is no part of our country in which one cannot form a beautiful local collection, and any young person who wants amusement, instruction, and benefit from two, three, or more weeks in the country can find all in catching butterflies and moths, arranging them, and studying them up.

Provide yourself first with two tools, a net and a poison bottle. The net may be made of any light material. I find the thinnest Swiss muslin best. Get a piece of iron wire, not as heavy as telegraph wire, bend it in a circle of about ten inches diameter, with the ends projecting from the circle two or three inches; lash this net frame to the end of a light stick four or five feet long. Sew the net on the wire. The net must be a bag whose depth is not quite the length of your arm—so deep that when you hold the wire in one hand you can easily reach the bottom with the bottle (to be described) in the other hand. Never touch wing of moth or butterfly with your fingers. The colors are in the dusty down (as you call it), which comes off at a touch. Get a glass bottle or vial, with large, open mouth, and cork which you can easily put in and take out. The bottles in which druggists usually get quinine are the most convenient. It should not be so large that you cannot easily carry it in your pocket. Let the druggist put in the bottle a half ounce of cyanide of potassium; on this pour water to the depth of about three-fourths of an inch, and then sprinkle in and mix gently and evenly enough plaster of Paris to form a thick cream, which will set in a cake in the bottom of the vial. Let it stand open an hour to set and dry, then wipe out the inside of the vial above the cake and keep it corked. This is the regular entomological poison bottle, used everywhere. An insect put in it dies quietly at once. It will last several months.

These two tools, the net and the poison bottle, are your catching and killing instruments. You know where to look for butterflies. Moths are vastly more numerous, and while equally beautiful, present more varieties of beauty than butterflies. They can be found by daylight in all kinds of weather, in the grass fields, in brush, in dark woods, sometimes on flowers. Many spend the daytime spread out, others with close

shut wings on the trunks of trees in dark woods. The night moths are more numerous and of great variety. They come around lamps, set out on verandas in the night, in great numbers. A European fashion is to spread on tree trunks a sirup made of brown sugar and rum, and visit them once in a while at night with net and lantern. Catch your moth in the net, take him out of it by cornering him with the open mouth of your poison bottle, so that you secure him unrubbed.

Now comes the work of stretching your moths. This is easy, but must be done carefully. Provide your own stretching boards. These can be made anywhere with hammer and nail and strips of wood. You want two flat strips of wood about seven-eighths or three-fourths of an inch thick and eight to fourteen inches long, nailed parallel to each other on another strip, so as to leave a narrow open space between the two parallel strips. Make two or three or more of these, with the slit or space between the strips of various widths, for large and small moths and butterflies. Make as many of them, with as various widths of slit, as your catches may demand. Take your moth by the feet, gently in your fingers, put a long pin down through his body, set the pin down in the slit of the stretching board so that the body of the moth will be at the top of the slit and the wings can be laid out flat on the boards on each side. Have ready narrow slips of white paper. Lay out one upper wing flat, raising it gently and carefully by using the point of a pin to draw it with, until the lower edge of this upper wing is nearly at a right angle with the body. Pin it there temporarily with one pin, carefully, while you draw up the under wing to a natural position, and pin that. Put a slip of paper over both wings, pinning one end above the upper and the other below the under wing, thus holding both wings flat on the stretching board. Take out the pins first put in the wings and let the paper do the holding. Treat the opposite wings in the same way. Put as many moths or butterflies on your stretching board as it will hold, and let them remain in a dry room for two, three, or more days, according to size of moths and dampness of climate. Put them in sunshine or near a stove to hasten drying. When dry, take off the slips of paper, lift the moth out by the pin through the body, and place him permanently in your collection.—Wm. C. Prime, in N. Y. Jour. of Commerce.

#### The Identification of Artificial Butter.

C. Fruwirth, of Vienna, Austria, in a letter to our cotemporary the *Country Gentleman*, states that the following proposition with regard to oleomargarine and artificial butters generally has been made in Germany. The indiscriminate coloring by some dye or pigment of all such articles had already been proposed and rejected. In consequence of this, Prof. Soxhlet, of Munich, has proposed a new treatment, which is worthy of attention. He proposes—and his proposition will be offered to the House of Representatives in Germany—to make it a law that all bogus butter must be mixed during the preparation with phenolphthalein, which is made out of one of the products of the dry distillation of tar, and one gramme of it will be enough for 100 kilogrammes of bogus butter. The butter can then be offered for sale colored yellow, or uncolored, or in any way desired, and the phenolphthalein will not be seen at all. But by adding a solution of soda, or ammonia and water (*liquor ammonii caustici*), or even a teaspoonful of water and the ash of a cigar, to a piece of butter the size of a bean, the whole of the butter will become a nice red if it is bogus butter, or if bogus butter is mixed with it.

It will be immediately seen that this is a proof which can be made by every policeman in any shop, by every guest in a dining room, etc. In your country it would be easy to enact that no butter shall go out of the factories to which has not been added the phenolphthalein. The internal revenue officers, which have to deal, since the first of November, 1886, with bogus butter, could very easily took at this point also.

#### Bag Bleaching.

Dr. C. Wurster gives a description, in a recent number of the *Berlin Papier Zeitung*, of a process for resolving chlorine gas and collecting the gas for reuse. He connected the different bleaching vats with lead pipes with water valves and sucked out the gas with a ventilator. All the parts of this apparatus were coated with paraffine, which resists the action of the gas. Between the vats and the ventilator was placed a lead cylinder, full of coke, with water dropping upon it, to prevent volatilization. A false bottom with small siphons, whose upper edges are cut off obliquely, forms the distributing apparatus. The original plan of using lime water or a solution of soda for absorption of the chlorine was found unnecessary, as water alone answered the purpose. The use of this apparatus makes it possible for the men to step upon the vats in ten minutes and obviates the hurtful effect of the gas upon the workmen's health and the rusting of the machinery, because the air which flows from the ventilator scarcely even smells of chlorine.



## SIMPLE PHOTOGRAPHIC AND PHOTO-MICROGRAPHIC APPARATUS.

A photographic outfit that will do very good execution may be purchased for a few dollars, but notwithstanding the small expense, many are deterred from making a beginning in photography on account of the first outlay.

While first class photographic instruments can be made only by makers having the greatest skill and large experience, an ordinary camera that will serve the purposes of the amateur may be made by the amateur himself with the expenditure of an insignificant sum for materials.

Figs. 1 to 12 show a camera tube, box, and tripod the materials of which cost less than a dollar. The construction is within the range of any one having a little mechanical ability. The camera is intended for 4 by 5 plates, therefore the size of the plate holder and the focal length of the tube will determine the size of the camera box. To avoid turning the camera or plate holder, the box is made square, and the inside dimensions of the plate holder are such as to permit of placing the plate either horizontally or vertically, according to the subject to be photographed. The plate holder is  $5\frac{1}{4}$  inches square inside, and is provided with a wooden back of sufficient thickness to support the hooks employed for holding the plate. There are four V-shaped wire hooks, *a*, at the bottom of the holder, two for receiving the end edge of the plate, and two farther apart, and arranged higher up, for receiving the side edge of the plate; and near the top of the holder there are three Z-shaped hooks, *a*, one in the center for engaging the end edge of the plate, and one near each side of the holder for receiving the side edge of the plate. The top of the frame is slotted, and the sides and bottom are grooved to receive the slide, which covers the plate before and after exposure. To the under surface of the upper part of the frame of the plate holder is attached a looped strip of elastic black cloth, such as broadcloth or beaver, which closes over the slot of the plate holder, as shown in Fig. 10, when the slide is withdrawn, and thus shuts out the light. The interior of the plate holder, as well as the slide, should be made dead black, by applying a varnish made by adding three or four drops of shellac varnish to one ounce of alcohol, and stirring in lampblack until the required blackness is secured.

The main frame of the camera box is made square, and is secured at right angles to the base board. The frame is provided with a narrow bead or ledge that will enter the front of the plate holder and exclude the light.

To the front of the frame are secured four trapezoidal pieces of pasteboard, of the form and size given in Fig. 6. These pieces of pasteboard are secured to each other and to the camera box frame by tape, glued on as shown. If the box is made of junk board, it may be nailed together with wire nails. In this manner a pyramidal box is formed which is strong, light, and compact. In the smaller end of the box is fitted the beveled centrally apertured block shown in Fig. 7. The aperture of this block must be made to fit the camera tube shown in Figs. 1 and 2, after having received a lining of plush or heavy felt.

The camera tube may consist of paper or metal. Paper answers well, and costs nothing. The internal diameter of the tube is determined by the diameter of the lenses. Ordinary meniscus spectacle lenses of eight inch focus are employed. These lenses are secured in place by paper rings, shown in Fig. 3, the inner rings being glued in place, the outer ones being made removable for convenience in cleaning the lenses. The lenses are arranged with their convex sides outward; the distance between them is  $1\frac{1}{4}$  inches, and in one side of the tube, half way between the lenses, is made a slot to receive the diaphragms, as shown in Figs. 1 and 2. Upon each side of the slot, within the tube, are secured flat rings, shown in Fig. 4, which together form a guide for the diaphragms, as shown in Fig. 2.

The tube is adjusted at the proper focal distance

from the plate by temporarily securing at the back of the box a piece of ground glass or tracing paper, in exactly the same plane as that occupied by the plate in the plate holder. The tube is then moved back and forth until a focus is obtained which shows the image fairly sharp throughout the field. In arranging for a fixed focus, it is perhaps best to favor the foreground rather than the distance. The tube should move with sufficient friction to prevent it from being easily displaced. By using a small diaphragm, it will be found unnecessary to focus each subject separately.

In Fig. 12 is shown a combination of cheap lenses devised by Mr. Henry Mead, which is effective for portraits and for other classes of work when focusing is admissible. It consists of two meniscus lenses, each of

good objective for photo-micrography. In photographing microscopic objects, it will be necessary to employ a focusing ground glass, and to focus very carefully by the aid of a magnifier.

Slow plates are preferable for this use, as they bring out the detail much better than fast plates. The time of exposure will vary with the object, from fifteen seconds to a minute or more.

Fig. 13 shows the arrangement of the lantern, the microscope, and the camera box. It will be noticed that the annular space in the end of the camera box around the microscope tube is stopped by a black cloth wound loosely around the microscope tube. This and other precautions are necessary for preventing the light from reaching the plate except through the object and the microscope. G. M. H.

## Pita.

According to a report of Consul Burchard, of Ruatan, in Honduras, the pita plant has never been cultivated, but grows wild in patches on the borders of rivers and lagoons. The stalks of the plant contain the fiber of commerce, and grow sometimes to a height of 12 feet. The Indians scrape off the hard skin of the stalk with a bamboo knife, and thus obtain the fibers which form the heart of the stalk. Another plan is to steep the stalks in water until the skin decomposes; but this is said to injure the fiber somewhat. In recent years machines have been devised to decorticate the fiber, but these have all been failures, owing to the fact that no machine has yet been invented capable of operating on a profitable scale. In Honduras the pita or "silk grass" fiber is used chiefly for thread, nets, fish line, and cordage. Samples of the

fiber sent to the United States and Europe have been manufactured into lace handkerchiefs, ribbons, and wigs. It is held to be a substitute for silk or linen; and if proper machinery were forthcoming, the wild pita fields of Honduras might be utilized in commerce. Consul Burchard indeed expresses the opinion that the fiber is destined to become a very important element in the future commerce and industry of this country.

## A Curiosity in Photometry.

It is interesting at the present day, when the photometry of gas and electric lights has been brought to some degree of perfection, to read of an expedient adopted in former times in Paris to control the quality of the street lamps. The method has very recently been made public. The Police Department of Paris, in whose charge the matter was placed, had paper patterns cut out representing what they considered the proper size, or profile, of a gas flame. These were furnished to their inspectors, who compared them with the flames of the street burners, and judged accordingly of their quality. In case of deficiency, fines were imposed. These fines were levied, and not collected until some 600,000 francs stood against the gas company. The method was so crude that the authorities did not venture to submit it to a court of law. The devisers of the plan overlooked the fact that a small flame may, and often does, give more light than a large one, and reduced it all to a question of size. Nevertheless, our present system is far from perfect, from analogous causes. Complaints of its inaccuracy have grown more frequent since the introduction of water gas, and several have appeared during the last year. It is known that a water gas that shows sixteen candles on the bar photometer is far from satisfactory, while a sixteen candle coal gas will always be accepted as of

good quality. The whiteness of the water gas flame probably introduces an error. This appears especially probable when we recollect that the standard of comparison is a candle having an extremely yellow flame. Polarization photometers have been little tried, and it is hardly known how efficiently they will act, but at this late day the absolute photometer has yet to be constructed. The effect of light on the human eye is the ultimate standard. This introduces a subjective element into the question that is very hard to cope with.





Fig. 13.—MICROSCOPE AND CAMERA ARRANGED FOR PHOTO-MICROGRAPHY.

$8\frac{1}{2}$  inch focus, having their convex sides arranged outwardly, and a plano-concave lens, 16 in. focus, arranged with its concave side against the concave side of the outer lens of the system. The plano-concave and the rear meniscus lenses are arranged  $1\frac{1}{2}$  inches apart. Diaphragms may be used as in the other case, and a box about 8 inches deep will be required.

The tripod is formed of a triangular centrally apertured board, to which are hinged three tapering wooden legs, by means of ordinary butt hinges, as shown in Fig. 11. The base of the camera box is secured to the tripod by means of an ordinary thumb screw.

This outfit will enable the amateur to cultivate his tastes, and learn much about photography. Dry plates will of course be used. They are procurable almost anywhere, and are inexpensive. As to the treatment of plates after exposure\* and printing and toning, the reader is referred to the works on the subject of photography. The amateur who possesses one of the microscopes described in a previous article of this



SIMPLE PHOTOGRAPHIC CAMERA.

series may arrange it for projection as described on page 393 of vol. lvi. of the SCIENTIFIC AMERICAN, and may insert the end of the microscope tube in the camera box above described, after removing the tube, and project the image of the microscopic object on the sensitive plate, and thus produce good negatives of the objects, from which prints may be made which will be interesting both to the operator and his friends. The eyepiece of the microscope referred to is a very

\* See SUPPLEMENT, No. 541.



## ENGINEERING INVENTION.

A lock for bolts of pistons has been patented by Messrs. Joseph Wornald and Joseph Wornald, Jr., of Missoula, Montana Ter. Combined with a fixed plate and studs is a lock plate, with circular slots adapted to engage the studs to hold the lock on the fixed plate, and projections on the rim of the lock plate engage one side of the bolt heads of the usual bolts, preventing the latter from turning. This invention has also been patented in Canada and in England.

## MISCELLANEOUS INVENTIONS.

A vehicle spring attachment has been patented by Mr. Stephen M. Wier, of New Haven, Conn. The invention consists in yokes resting upon or suspended from the axles near the wheel bearings, with stirrups for receiving the ends of the springs, the stirrups capable of springing to permit of the elongation of the spring due to its compression.

An ironing table has been patented by Mr. Franklin P. Buraw, of Hazleton, Pa. Its construction is such that the legs may be folded to have the device occupy only a small space when not in use, but the several connections are of such a character that when the table is opened and in position for use it will be perfectly steady and cannot accidentally collapse.

A drip trough for doors or windows has been patented by Mr. William W. Pitman, of Waseon County, near Smith's Mill, Minn. The sill is made with a gutter or groove and a channel leading thence outward, a tube fitting at its inner end within the outer end of the channel, and having an outlet opening with a plug or knob.

A combined hook and clasp for horse collars has been patented by Mr. Louis T. Anderson, of Carroll, Iowa. The invention consists of a clasp made to be slipped upon the rim or front roll of a horse collar, with a tongue or hook stamped from the material of the clasp, making a cheap and convenient device for attaching sweat pads to the collars.

A wagon box lock has been patented by Mr. Nathan O. Calkins, of Elm Creek, Nebraska. It is for fastening an auxiliary wagon box on top of an ordinary one, and do away with the employment of staves and staples for such purpose, the lock consisting of a hook latch of peculiar construction and a retaining device for holding the latch in locked position.

A druggist's mortar has been patented by Mr. Edmund G. Purdy, of Ballston Spa, New York. It has one or more lugs projecting from its outer surface, and an annular frame is to be used therewith adapted to partly inclose the mortar, and having recesses for receiving the lugs, thus holding the mortar in a fixed position while in use.

A vehicle wheel has been patented by Mr. Robert A. Townsend, of Sibi, Beloochistan, India. The invention covers the application of an inclined plane at the hub to lengthen the radii of the wheel to compress the spokes, felloes, and rim, with tire jacks, operated by the spokes, to bridge the space between the felloes caused by the shrinkage of the latter.

A mouth harmonica has been patented by Mr. John F. Stratton, of Brooklyn, N. Y. It is to be played in the same manner as the mouth harmonicas now in general use, but is provided with an upper set of reeds, of which each reed forms a chord with the corresponding reed of the lower set, making a rich and harmonic tone when played, forming a duet.

An accordion has likewise been patented by the same inventor. It is constructed in accordance with the principle noted in the preceding invention, having an additional set of bass reeds tuned to a higher or lower pitch than the ordinary bass reeds, but in harmony therewith, so as to produce harmony in the accompaniment when the accordion is played.

A cider press has been patented by Mr. Hiram P. Latham, of Denver, Col. A series of rollers is journaled in a case, combined with which is a feeding device of a tube opening to the rollers at the side of the case, with a hopper, a conveyor screw rotating within the tube to force the substances to be ground to the rollers, and other novel features, the press being also adapted for pressing and grinding other substances.

A rinsing and drying device for dishes and other articles of table use has been patented by Mary Purvis, of Plainview, Minn. It is designed to be used after the dishes have been washed, when they are placed in particular places or on racks provided therefor within a case, in such way that hot water poured through an aperture into a pan in which the utensil stands will thoroughly rinse and quickly dry them.

A flour bolting reel has been patented by Mr. Francis E. McMaster, of Millburn, Pa. The reel is provided with external cloth flaps at one edge of its periphery, in combination with the bolt chest, the flaps to brush the outer face of the bolting cloth, and also brush the bolted material from the walls of the chest, the device being simple and inexpensive, while making the action of the reel more quick and effective.

A mattress has been patented by Mr. Earnest Brooks, of New York City. The invention provides a detachable strip of non-heat-conducting material to protect the top and bottom of the mattress, such material being of rubber or paper backed with linen or otherwise, or other suitable substance, whereby a thinner mattress may be used, and cold will not so readily penetrate it.

A pocket knife has been patented by Mr. Carl Hollweg, of Barmen, Prussia, Germany. The handle has side plates immovable with respect to each other, there being also a locking lug and outer independent handle, with other novel features, whereby the blades can all be independently opened and closed, or locked in position, without touching them, and no springs are employed.

A kindergarten game for teaching children has been patented by Imogen B. Oakley, of Pittsburg, Pa. Combined with a copy book having illustrated objects and their names in printed letters are

detached cut or stamped letters made to form facsimiles of the printed letters in the book, the child forming the names or titles from the loose cut or stamped letters.

A gas burner has been patented by Mr. Josiah Burgess, of Zanesville, Ohio. It is principally designed to produce and burn gas from petroleum and its products, and for the burning of other gases, in laundries, coffee wasters, stove heaters, etc., providing means for vaporizing the oil supplied by a tank and distributing it through suitable burners in properly regulated amounts.

An improvement in folding furniture has been patented by Mr. Joseph B. Brolaski, of St. Louis, Mo. The invention covers especially the construction of an improved bureau, which may be easily knocked down and its parts closely packed, and in which the joints may be readily tightened or loosened in case of shrinkage or swelling of the different pieces, thus making each joint adjustable.

An adjustable coat holder has been patented by Mr. Hans Christian, of Vienna, Austria-Hungary. It consists of a single length of wire bent to form two sets of parallel bars, the ends of the wire being coiled at the inner ends of the bars to form hooks, in connection with shoulder supports that can be moved inward and outward to correspond to the width of the garment at the shoulders.

A device for converting motion has been patented by Mr. John W. Ledyard, of New York City. This invention covers a novel construction for converting reciprocating into rotary motion, which is designed to give more power with the same length of stroke, and so that the dead centers will be more easily and smoothly passed than when a crank is used in the ordinary way.

A wire cloth delivering reel has been patented by Mr. Elias E. Ratekin, of Kansas City, Mo. It has a vertical body and a vertical roll holder, with a horizontal pivot or shaft connecting the holder to the body, whereby the holder may be swung from a vertical to a horizontal position, a locking device upon the body engaging and holding the roll holder in either of its two positions, with various other novel features.

A pitman or pump rod has been patented by Mr. John F. Loomis, of Shelby, Iowa. It is designed especially for windmills, and the invention consists in the interposition of a spring or elastic cushion in the direction of its length, to render the rod elastic, and take up excessive strain and jar, causing a shorter stroke for the pump piston in proportion to the increased speed of the wheel.

A hair or mustache curler has been patented by Mr. Morris N. Posner, of New York City. The main body part of the device has a slot in one end, with a spring-pressed clamp bar mounted on the slotted end and normally pressed down thereon, to firmly hold the mustache or tuft of hair while it is being wound around the device, the spring clamp being readily lifted by pressing with the thumb on its rear end.

A vehicle tongue support has been patented by Mr. Alva N. Books, of Alpha, Mo. Two parallel and spaced semi-elliptical springs are pivoted to the under surface of the tongue, their inner ends bearing against the under side of the forward axle at each side of the king bolt, and so held adjustably that they will support the pole in any desired position, relieving the horse from such weight.

A road grader and leveler has been patented by Mr. John Skinner, of Newman, Ill. This invention covers an improvement on a former patented invention of the same inventor, providing a better method of elevating and lowering the framework carrying the harrow teeth and scraper, so that the machine can be easily supported at any desired height from the ground.

A coin or ticket receiving turnstile has been patented by Mr. Walter Peake, of New York City. The turnstile post has a cam and locking plate, combined with a locking dog and two pistons, one connected to the dog and the other acted upon directly by the cam, with other features, whereby the turnstile is operated only when a ticket, coin, or check, or other device, is dropped or pressed into the lock mechanism.

A washing machine has been patented by Mr. George W. Wilson, of Lanesborough, Minn. The tub has a false bottom, and secured to its side is a support for a lever designed to operate a pneumatic washing head or pounder in the tub, the action of which not only squeezes the clothes, but by pressure and suction forces air and water through them to quickly free them from dirt.

Saliva-proof mouth pieces for cigarettes form the subject of a patent issued to Mr. Joseph B. Underwood, of Fayetteville, N. C. The invention consists of a new method and machine to do work heretofore done by hand, the cigarette being made to rotate on its own axis in contact with a surface supplied with the material to be applied, such as paraffine, varnish, etc.

A horseshoe has been patented by Mr. Charles J. Le Roy, of St. Louis, Mo. It has a calk recess open at one end, with an independent calk fitting therein, there being a longitudinal groove between the calk and adjacent side of the calk recess, and the groove being enlarged and closed at its inner end, whereby a nail driven into the recess will have its point bent over or clinched against the closed end of the groove.

A photographic camera has been patented by Messrs. Nicholas Schroder and Edward G. Adams, of Brooklyn, N. Y. The patent provides for a construction whereby the front and back of the camera may be angled in various directions to adapt the focus to parts of the subject not lying in the same plane. An adjustable or sliding base frame may be dispensed with, while making a light and efficient camera and plate holder.

A device for swaging insertible saw teeth has been patented by Messrs. Neils H. Wheeler and Neil M. Newhouse, of Corvallis, Oregon. It is for restoring old and unserviceable teeth, the swage blocks

being adjustable in relation to each other for the proper size of tooth, and firmly seated in a vise or socket, when the old tooth, at a cherry red heat, is placed in position, and, by the movement of a cam-headed lever, is drawn and swaged to the proper configuration at the point, receiving a roll temper.

A wheel and axle form the subject of a patent issued to Mr. Henry Q. Maurino, of Albuquerque, New Mexico. The invention provides a wheel on which the tire may be placed without heating, and tightened when necessary, there being devices for expanding the felly sections by endwise pressure of the spokes at the felly joints, with retaining washers or plates held at the faces of the wheel to overlap the ends of the spokes and the felly sections.

A machine for making paragon umbrella ribs has been patented by Mr. Daniel M. Redmond, of Philadelphia, Pa. It is designed to flatten, re-enforce, and perforate the ribs in continuous lengths, instead of in separate pieces, as has been heretofore done, in connection with a method of manufacture by which they will also be tempered, annealed, and tested in the operation, without the aid of skilled labor, the machine presenting many novel features of construction and arrangement of parts.

An adding machine has been patented by Mr. James Richardson, of Tarrytown, N. Y. It has two series of numbered wheels, a series of numbered keys, with means for imparting motion to the numbered wheels from the keys, mechanism for insuring the operation of the numbered wheels in succession and for returning the wheels and the wheel-moving mechanism to the point of starting, together with a registering and summing mechanism and a disk for registering the number of the addition.

An improved card clothed roller and a machine for making card clothing form the subject of two patents issued to Mr. Ernst Gessner, of Aue, Saxony, Germany. A strip of card clothing having its rows of teeth set obliquely to its length is wound spirally on the roller so as to bring its rows of teeth parallel with the axis of the roller and the arms of the teeth in radial position, improving the working effect and enabling the teeth to better withstand the working strain. The machine patented is for making the card clothing with the card teeth set in rows arranged obliquely to the length of the band.

SCIENTIFIC AMERICAN  
BUILDING EDITION.

## JULY NUMBER.

## TABLE OF CONTENTS.

1. Plate in Colors of a Two Thousand Five Hundred Dollar Dwelling, at Montclair, N. J., with floor plans, also sheet of details, specifications, bills of estimate, etc.
2. Plate in Colors of a Handsome City Residence at Kansas City, Mo., costing Seven Thousand Five Hundred Dollars, with plans, specifications, sheet of details, etc.
3. Page drawing in perspective of an Elegant Stone Residence, corner 19th Street and Sixth Avenue, New York City.
4. An Attractive Residence at Providence, Rhode Island, with perspective and plans. Cost, Five Thousand Five Hundred Dollars.
5. Dwelling at Jersey City, N. J., with elevations and floor plans. Cost, Three Thousand Five Hundred Dollars.
6. Page drawing showing floor plans and elevations of a very comfortable Dwelling at Flatbush, N. Y., costing Three Thousand Seven Hundred Dollars.
7. Drawing in perspective of a Dwelling at East New York, Cost, about Three Thousand Five Hundred Dollars.
8. A Modern English Dwelling, with half page perspective drawing.
9. Drawing in perspective of a Residence at East Orange, N. J., costing about Four Thousand Five Hundred Dollars.
10. Engraving of the Bourse at Havre, France.
11. Hotel and Office Building, River Side Avenue, Spokane Falls, W. T. Quarter page engraving.
12. The new facade of the magnificent Cathedral of the Duomo of Florence. Full page engraving. Portrait of Donatello, the sculptor.
13. The Manchester Royal Jubilee Exhibition, with nine large engravings, covering four pages, including specimens of "Old Manchester and Salford."
14. A Residence of Moderate Cost, in St. Louis Park, Minn., with perspective and floor plans.
15. A substantial City Residence at Chicago. Quarter page engraving and floor plan.
16. Design for Young Men's Association Building, Buffalo, N. Y. Half page drawing.
17. Illustrations of Memorable Buildings in Rouen, France, including the front of the Cathedral of Notre Dame and the portal of St. Ouen. Three engravings.
18. Drawings in perspective of Three Comfortable Dwellings of Moderate Cost, at Cambridge, Mass.
19. The New Post Office, Springfield, Ohio. Quarter page engraving.
20. Miscellaneous Contents: Women as Architects. Terra Cotta Panels.—Acoustic Effects of the Britannia Bridge.—Regulation of Building in Boston.—Improved Camera Clamp and Tripod Head, illustrated.—Joists in Woodwork, with illustrations.—Preventive for Dry Rot.—Great California Dam.—Plumbing and Drainage.—Varying Meters, illustrated.—Sketch of Life of M. Ruprich-Robert, the distinguished French Architect.—Home Interests.—Pa Crusta, a new style of interior decoration.—Algerian Marbles.—Ancient Relics at Sidon.—Portrait of Henri Jacotot, raiser of Gloire de Dijon.—New Hardy Passion Flower, illustrated.—Effects of Change of Temperature on Girders.—The Howe Brother Farm, with two illustrations, showing method of heating brooders.—Air Filter, illustrated.—About Plumbing.—Common Use of Woods in England.—Sandstone as a Building Stone.—Hall Patent Sheathing, illustrated.—Red Granite.—A Novel Weather Vane, illustrated.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming, practically, a large and splendid MAGAZINE OF ARCHITECTURE, richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects. The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural publication in the world. Sold by all newsdealers.

MUNN &amp; CO., PUBLISHERS.

961 Broadway, New York.

## Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

All Books, App., etc. cheap. School of Electricity, N. Y. Chemist of 15 years' experience wants position. Low salary. References. P., box 204, New York City.

The new "Trantwine" contains articles on machine rock drills, air compressors, and modern explosives. The former gives 27 sectional views of some of the more prominent modern drills.

For Sale—One 100 H. P. Ducky Engine.—On account of our putting in a 300 H. P. Corliss engine (July 1) we offer for sale a Ducky engine, 100 H. P., in first class order. Can be seen running at factory of Seabury & Johnson, East Orange, N. J.

Electric Mats, Burglar Alarm, under Carpets. Only Security. (Thieves remove panel or glass. Old Alarms worthless.) Invaluable. Stores, Offices, Door Open. S. S. Applegate, Camden, N. J.

Stationary and boat engines, boilers. Best and cheapest. 1 to 15 H. P. Washburn Engine Co., Medina, Ohio.

Press for Sale—Quick acting. Hole in bed 8x5; punches to center of 18 in. sheet; 2 1/2 in. shaft; also four spindle Drill. A few second-hand engines in first-class condition. B. W. Payne & Sons, Elmira, N. Y.

For the latest improved diamond prospecting drills, address the M. C. Bullock Mfg. Co., 125 Jackson St., Chicago, Ill.

The Australian-American Trading Co., 30 Collins St., West Melbourne. Sole agencies for American novelties desired. Correspondence solicited. Care of Henry W. Peabody & Co., Boston.

The Railroad Gazette, handsomely illustrated, published weekly, at 73 Broadway, New York. Specimen copies free. Send for catalogue of railroad books.

The Knowles Steam Pump Works, 113 Federal St., Boston, and 95 Liberty St., New York, have just issued a new catalogue, in which are many new and improved forms of Pumping Machinery of the single and duplex, steam and power type. This catalogue will be mailed free of charge on application.

Link Belting and Wheels. Link Belt M. Co., Chicago. Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J.

Woodworking Machinery of all kinds. The Bental & Mergendall Co., 116 Fourth St., Hamilton, O.

Nickel Plating.—Sole manufacturers cast nickel anodes, pure nickel salts, polishing compositions, etc. \$100 "Little Wonder." A perfect Electro Plating Machine. Sole manufacturers of the new Dip Lacquer Kristaline. Complete outfit for plating, etc. Hanson, Van Winkle & Co., Newark, N. J., and 92 and 94 Liberty St., New York.

Iron Planer, Lathe, Drill, and other machine tools of modern design. New Haven Mfg. Co., New Haven, Conn.

Supplement Catalogue.—Persons in pursuit of information of any special engineering, mechanical, or scientific subject, can have catalogues of contents of the SCIENTIFIC AMERICAN SUPPLEMENT sent to them free. The SUPPLEMENT contains lengthy articles embracing the whole range of engineering, mechanics, and physical sciences. Address Munn & Co., Publishers, New York.

Use Alnsworth's Belt Clamp. See advt. next issue.

We are sole manufacturers of the Fibrous Asbestos Removable Pipe and Boiler Coverings. We make pure asbestos goods of all kinds. The Chalmers-Spence Co., 419 and 421 East 8th Street, New York.

Steam Hammers, Improved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

50,000 Emerson's 1887 Book of superior saws, with Supplement, sent free to all Sawyers and Lumbermen. Address Emerson, Smith & Co., Limited, Beaver Falls, Pa., U. S. A.

Friction Clutch Pulleys. D. Frisbie & Co., N. Y. city. "How to Keep Boilers Clean." Send your address for free 65 page book. Jas. C. Hotchkiss, 120 Liberty St., N. Y.

The Holly Manufacturing Co., of Lockport, N. Y., will send their pamphlet, describing water works machinery, and containing reports of tests, on application.

Timber Gaining Machine. All kinds Wood Working Machinery. C. B. Rogers & Co., Norwich, Conn.

Double boring machines. Double spindle shaping machines. Rollstone Machine Co., Fitchburg, Mass.

Iron and Steel Wire, Wire Rope, Wire Rope Trays. Trenton Iron Company, Trenton, N. J.

Astronomical Telescopes, from 6" to largest size. Observatory Domes, all sizes. Warner & Swasey, Cleveland, O.

Split Pulleys at low prices, and of same strength and appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.

Send for new and complete catalogue of Scientific Books for sale by Munn & Co., 361 Broadway, N. Y. Free on application.

## NEW BOOKS AND PUBLICATIONS.

MCCARTY'S ANNUAL STATISTICIAN. 1887. Pp. 650. San Francisco, Cal.: L. P. McCarty.

This is the eleventh edition of Mr. McCarty's work, each issue being more full and complete than its predecessor. It is a sort of *compendium gauthier* of matters pertaining to history, politics, geography, and trade, with much curious and useful information not classifiable under either of these headings, and to a large circle of readers cannot fail to fill a valuable place as a ready reference book.

IMPROVED PLUMBING APPLIANCES. By J. Pickering Putnam. Pp. 129; 94 illustrations. New York: William T. Comstock.

This book treats only of lavatories, including wash basins, bath tubs, and kitchen and pantry sinks, together with water closets, traps, and waste pipes. It presents forcibly the need of the best work in plumbing, with all the work so constructed that inspection will be easy, and urges the need of greater simplicity than has lately obtained in the fittings adopted in some of our more expensive dwellings. Illustrations are given of some of the latest patterns of water closet flushing arrangements, but the writer, who is an archi-



test, and has developed a special device of his own of this kind, naturally argues strongly in favor of his own device.

#### THE CONVERSION OF HEAT INTO WORK. By William Anderson. London: Whittaker & Co. New York: D. Van Nostrand.

The simple and direct but extremely interesting way in which an ordinarily complicated subject is here presented will doubtless render this book of exceptional value to young mechanics who know little of the theoretical side of their business, and to other students who have to "dig out" their education from books, without the aid of teachers. Although now published as a practical handbook on heat engines, it contains but little matter in addition to that which appeared in the original form in which it was published, as lectures before the Society of Arts and Manufactures, London, which were printed in six successive numbers of the SCIENTIFIC AMERICAN SUPPLEMENT in the latter part of 1885.

#### A HISTORY OF SALT LAKE CITY AND ITS FOUNDERS. Salt Lake City, Utah: Edward W. Tullidge.

This is a handsome octavo volume of nearly 1,100 pages, profusely illustrated with fine steel engravings of the principal Mormon notables from 1840 to the present time, with biographical sketches. It is in fact a history of Mormonism and its growth and development in Utah, written by "authority of the Council and under supervision of its Committee on Revision," and therefore giving a picture of Mormonism in the most favorable light in which it is possible to present the institution to the public. There are too many outside evidences of material prosperity and thrift everywhere to be seen in the resourceful valley where the Mormon emigrants from Illinois and Missouri began to make their home in July, 1847, and the vitality of the community has been too plainly manifested on many occasions, for any one easily to escape the conclusion that the "Mormon question," as it is called, is still one of no insignificant importance. It is no part of our purpose to discuss the matter, but just why and how it has become of such material significance is probably more fully explained in this volume than in any other one work published.

*The British Guiana Directory for 1887*, published by C. K. Jardine, Demerara, cannot fail to be a valuable aid to such of our merchants and manufacturers as are seeking to extend trade in that exceedingly fertile and resourceful tract of 600,000 square miles lying just under the equator, on the northeast coast of South America. The book gives full details of all departments of the little government, with classified directory for the principal trades in different cities, the prominent country estates, etc.

\*Any of the above books may be purchased through this office. Send for new catalogue just published. Address Munn & Co., 361 Broadway, N. Y.

## Notes & Queries

### HINTS TO CORRESPONDENTS.

**Names and Address** must accompany all letters, or no attention will be paid thereto. This is for our information, and not for publication.  
**References** to former articles or answers should give date of paper and page or number of question.  
**Inquiries** not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all, either by letter or in this department, each must take his turn.  
**Special Written Information** on matters of personal rather than general interest cannot be expected without remuneration.  
**Scientific American Supplements** referred to may be had at the office. Price 10 cents each.  
**Books** referred to promptly supplied on receipt of price.  
**Minerals** sent for examination should be distinctly marked or labeled.

(1) W. M. L. writes: 1. In building an eight light dynamo as illustrated in SCIENTIFIC AMERICAN, April 23 and 30, can I substitute brass instead of bronze for making sleeve A, flange B, and cylinder E, Fig. 6 (SCIENTIFIC AMERICAN, April 30), also for yoke-holding shaft, or only make cylinder E of bronze and the rest of brass. A. Brass may be used, but bronze is preferred on account of its hardness and durability. 2. Does it make any difference in the winding of the field magnet whether I wind both posts right or left handed, or should they be wound different? A. Wind so that if placed endways the direction would be uniform. Both must be wound either right or left handed. 3. How can I attach machine to wooden base? A. Drill and tap the polar extremities, and insert tap bolts through the wooden base. 4. What is the best wood to use for the armature core? A. Well seasoned mahogany or maple. 5. What are the wedges made of that are used for dividing the coils on the armature? A. Hard rubber, vulcanized fiber, hard wood, or bone.

(2) R. T. asks: In regard to pumping cold water into a boiler when the water is low and the fires heated, is it not the gas that is generated in coming in contact with the hot iron that causes an explosion? A. It is dangerous to pump cold or hot water into a boiler with the line of water below the top flues; at such times the flues out of water may become red hot, as also the sides of the boiler above the water. Pumping up the boiler at such times largely increases the generation of steam, possibly carrying the pressure up to the point of rupture. The theory that explosions are thus caused by gas formation is in no way sustained.

(3) C. H. D. & Co. ask the ingredients of a solution in which to steep burlap or jute bags in order to make them more durable when used for transporting acid fertilizers, such as dissolved phosphate rock. A. Plunge the bagging into a solution, at 145° Fah., and leave for an hour, the solution consisting of sulphate of alumina 3/4 pounds, water 5/4 gallons, and

borate of lime 3/4 pounds. The borate of lime is added after the sulphate of alumina has dissolved, and the whole decanted when settled. After taking out of this bath, the textiles are put into a second bath, composed of 2 1/2 pounds resinous soap and 3/4 pounds Marseilles soap dissolved in 5/4 gallons water and carried to the boiling point. At the end of ten minutes the bags are allowed to drip, are next dried, and then rewashed and dried. Bagging made in this way, it is claimed, will resist the action of acids or chemicals.

(4) E. T. H. asks how to make a mahogany stain for wood, and a varnish to coat it to represent a polish. A. The following is a dark stain: Boil 1/2 pound of madder and 2 ounces logwood chips in a gallon of water, and brush over while hot; when dry, go over the whole with a pearl ash solution, 2 drachms to the quart. Or put 2 ounces dragon's blood, bruised, into a quart of oil of turpentine, let the bottle stand in a warm place, shake frequently, and when dissolved, steep the work in the mixture. To polish, take a piece of pumice stone and water, and pass repeatedly over the work until the rising of the grain is cut down. Then take powdered tripoli and boiled linseed oil, and polish the work to a bright surface.

(5) H. W. F. asks: 1. What cement, either liquid or otherwise, can I use to mend china so as to hold hot substances, and the cement to be transparent or white? A. See article on cements in SCIENTIFIC AMERICAN SUPPLEMENT, No. 158, for this information. 2. How is oak finished as "antique oak"? Is it possible to do over oak furniture so that it will be antique? A. By intensifying the stain, the oak can be made to resemble the antique article. New furniture retained has that appearance. 3. What is the cause of the "gapes" in chickens, etc., and what can be used to prevent and cure it? A. Camphor pills, it is said, will cure this disease. Sulphur is also used. 4. How do you multiply hyacinth bulbs? A. They multiply from the small bulb which form at the base of the large ones.

(6) H. A. L. and others.—Your question has been many times answered. Try and look a little more closely into the exact terms of the problem. No part of the periphery of a wheel of a wagon moving along a road travels faster around its axis than another part. The axis moves along the road with the mean speed of the top and bottom of the wheel. The top of the wheel moves twice as fast as the wagon. *Per contra*, the periphery of the wheel is during one half of its revolution gaining, and during the other half losing speed, as compared with the forward motion of wagon and axle, so that the bottom of the wheel, or part in contact with the ground, does not move in a measurement of this onward movement.—A snake climbs a tree that is small enough to allow of its peculiar manipulation, by a spiral movement around the trunk or a return bending of its coils nearly half way around, by which the snake obtains a grip. Their favorite trees are the kind that have low limbs, which give them a natural rest.—For the manufacture of steel see back numbers of SCIENTIFIC AMERICAN SUPPLEMENT.

(7) W. J. B. writes: Referring to article in SCIENTIFIC AMERICAN, April 23, 1887, upon eight light dynamo, will you please inform us through your paper: 1. What size of wire and how many layers to wind upon field magnet to make a plain series machine of it, using but one strand for conductor? A. Use eight layers of No. 12 (Am. W. G.) wire on each leg of the magnet. 2. What changes will be required to make it operate 12 standard 16 candle power lamps instead of 8? A. Put coarser wire on the armature, say No. 18, and increase the speed, and increase all the dimensions of the machine about 20 per cent.

(8) P. S. asks: How many gallons of water per hour will a 3 inch pipe line 7,000 feet long deliver into a tank, the point of delivery being 38 feet above ground and the head of water being 13 feet higher than point of delivery? A. 1,400 gallons per hour.

(9) R. F. asks how large to make a balloon and of what material, to lift 5 pounds. A. You will require a globular balloon of 7 1/2 feet diameter when filled with the carbureted hydrogen of your gas works to lift 5 pounds and the weight of the balloon of say 2 pounds. For material use strong tissue paper or Chinese silk well varnished with rubber varnish. See Balloon Making, SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 249, 413.

(10) G. K. G. asks: What will remove bicycle oil from corduroy without leaving a stain? A. Use ether or a mixture of ether and ammonia. Apply in a circle all around the stain, and sponge off the spot last of all.

(11) H. K. asks (1) the most practical method for making brass signs. A. Use nitric acid to eat into the metal. 2. How to permanently blacken the letters and scroll work? A. Mix asphaltum, brown japan, and lampblack into a putty-like mass, and then fill in the spaces, finally cleaning the edges with turpentine.

(12) S. O. N. writes: We have a driven well about 25 feet deep, with seven feet of water in it, but it does not pump easy. We think the point is in clay, and we cannot turn the pipe in ground. Can you suggest a way to make the water flow more freely—like exploding a dynamite cartridge in it? A. The pipe should either be drawn up so as to allow the strainer to receive the surface water lying upon the clay, or be driven deeper, to reach the next sand stratum, which may give a better supply. It will be of no service to torpedo the well in the clay. Besides, your point should have a strainer which precludes the use of a torpedo without first withdrawing the tube. Better drive deeper and find what is below the clay.

(13) J. J. asks the best way to tin tempered steel (small pieces) with a smooth thin coating without injuring temper or getting too hard. I have first cleaned the pieces in a hot solution of potash, then put them in diluted muriatic acid and then in zinc acid, before going into the tin, but cannot get them smooth and even. A. Your manipulation appears to be right, only that the surfaces should have a half polish or be quite smooth. Also the tin bath should have a clean surface, which can be made by sprinkling a little pow-

dered sal ammoniac upon the surface and skimming. Have the tin pretty hot and draw the pieces slowly out of the tin.

(14) E. P. asks: How are photographs on boxwood obtained? A. See SCIENTIFIC AMERICAN SUPPLEMENT, No. 429, page 630, also No. 584, page 932.

(15) C. E. E. asks how to make an enamel on steel, one that will dry quick and black. A. Use japan varnish and bake in an oven at 250° temperature.

(16) J. M. L. asks what to put in common coal tar to make it adhere to iron better than it does when simply boiled, and then applied. A. Mix with pulverized plumbago or lampblack. Thin with benzine if necessary. If color is no object, use Prince's metallic paint.

(17) H. S. sends a plant to be named, and asks whether it has any medicinal properties. A. The plant is a species of elder, *Sambucus glauca*. Its medicinal properties, if it has any, are probably the same as those of the eastern species, the flowers of which have been reported diaphoretic and diuretic, the berries aperient and emetic, the bark purgative, and, in small doses, diobstruent.

(18) W. S. asks: What is the greatest height at which a siphon will work, and the largest pipe that can be used therefor? A. There is no limit to the capacity of a pipe for a siphon. The greatest height depends upon the pressure of the air. It may be 33 feet, practically 28 to 30 feet.

(19) G. S. D. asks how hair clippers are ground or sharpened, whether on flat surface or between the teeth, and what is used to sharpen them with. A. Never sharpen the clippers on the flat side. Always on the bevel side. Use Washita or Arkansas stone and oil. You can buy the stone in long sticks, 1/4 inch diameter, through the hardware trade.

(20) P. & S. ask as to the feasibility of running an upright shaft direct from engine, through a six story building and connecting with it shafts on each floor by gearing. A. Vertical driving shafts in mills are only to be tolerated as a necessity, or as turbine shafts. The step of a long vertical shaft is a source of constant trouble, which added to the noise has about driven the system from present mechanical practice.

(21) H. M. D.—Six inch copper pipe may be bent to a radius of 3 or 4 feet by filling, after annealing, with resin. Allow the resin to cool, and bend slightly over a curved block of wood hollowed out, so that the pipe will bear half way round to keep it from flattening. Bend a little, then melt the resin out and anneal again. You may have to do this two or three times.

(22) F. E. writes: I wish to make a wire rheostat with resistance of 3,000 ohms, divided into 10 divisions or more—or 15. What size wire will I have to use to put 200 ohms resistance in each coil, and how much to each coil? Also give same with 300 ohms resistance to each coil. A. Of No. 35 German silver wire, one pound gives about 8,196 ohms resistance. Therefore one twenty-seventh pound will give you about 300 ohms, and one fortieth pound will give about 300 ohms. The exact resistance of each coil has to be determined experimentally. One pound of No. 40 wire gives about 41,948 ohms, so much less of this, about one-fifth the above amounts, would answer.

(23) C. H. G. wishes further directions about making a kite without a tail, such as was described in SUPPLEMENT, No. 595. A. The directions for making the bow, which you do not seem to understand, read: "The bow . . . consists of two pieces of oiled, each 5/4 units in length, that form, through their union, a total length of 7 units." This simply means that the two ends of the oiled that are to form the center of the bow should be lapped over each other to a sufficient extent to make the entire length of the bow when the two pieces are joined seven-tenths the length of the central stick.

(24) G. C. H. asks: 1. What is the best steel for making compass needles, and what temper will they require before magnetization, and what is the best shape to make them? A. Use cast steel, hardened and drawn to a purple. The straight bar form is probably the best. 2. Would a heavy coiled flat spring, say 3/4 inch thick and 6 inches wide and 30 feet long, be eight times as strong as one one-sixteenth inch thick, 3 inches wide, and the same length as the first? A. It would be more than eight times as strong. 3. Will the lighter spring lift 150 pounds? A. You have left out the element of time and distance. It will lift 150 pounds if connected with the weight by suitable mechanism.

(25) D. M. G. writes: In the article "Inexpensive Arc Lamp," in the June 11, 1887, number, what kind of a battery can be used? Will a telegraph battery answer, and how many? Where can I get the carbons, in Cleveland? A. It will require from 25 to 50 Grove or Bunsen cells. The ordinary telegraph battery will not answer. You can get carbons from any house dealing in electrical materials.

(26) J. D. McC. asks: 1. In SCIENTIFIC AMERICAN SUPPLEMENT, No. 160, article on induction coils, what is the object gained by having the secondary coil in two sections, with insulating resin between them? A. The construction in sections is for the purpose of more effectually separating those layers of the coil having the greatest differences of potential, so as to prevent sparks jumping across and destroying the insulating material. 2. Is there any good reason for preferring naked wire to silk-covered wire, except its greater cheapness? A. Naked wire lies closer and is cheaper than covered wire; no other reason exists for its employment.

(27) O. R. asks: 1. What is a good glue to use in making camera bellows? Ordinary glue becomes hard and the rubber cloth breaks. A. Use rubber cement. See "Cements," in SCIENTIFIC AMERICAN SUPPLEMENT, No. 158. 2. A developing formula in which quinol is used in place of pyro? A. You probably refer to the hydroquinone developer. The formula is as follows: A. Water 80 cubic centimeters, hydroquinone 1 to 2 grammes. B. Saturated solution of

carbonate of ammonia in water. To 8 parts of A add 1 part of B.

(28) W. D. B. S. asks: 1. Is there any difference in the lifting power of an elevator rope or ropes when the rope is passed through an eye, and the two ends attached to the drum, and when the rope is separated and attached in two places on the crosshead of the elevator, the ropes being all of one size? A. There is no difference. 2. What is the strain on a rope that two men are pulling on, one at each end, supposing one pulls 200 pounds one way, and the other pulls 200 the other way? A. The strain is 300 pounds.

(29) B. P. G. writes: About four years ago a young man in this place boiled a hen's egg and put it away. On breaking it open the other day, he found that everything in it had shrunk to a mass about one-twentieth the size of the egg, almost perfectly egg shaped. It looks like a piece of amber, being most beautifully translucent. A. The white of eggs contains about 85 per cent of water and 12 per cent of albumen. By boiling, the albumen is coagulated, but without much if any loss of water. By lapse of time the water gradually evaporates, and the result spoken of was probably due to this evaporation.

(30) Subscriber asks: Has it been definitely ascertained yet what caused the sinking of the Oregon? A. It was caused by collision with a vessel believed to be a coal schooner.

(31) W. S. asks: Does the brake of a car wheel when set up so as to nearly but not quite cause the wheel to slide, stop a train quicker than when the wheel slides? A. Yes. If the wheel is kept from rotating, the part in contact with the rail becomes polished and slides easily. If allowed to slowly turn, a new surface is continually presented to the rail. The latter practice stops the car quicker.

### TO INVENTORS.

An experience of forty years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequalled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

## INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

June 21, 1887,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

Atomizer, A. P. Lightbill.....	305,295
Awnings, device for operating, T. Charroh.....	305,299
Axle, R. Gracer.....	305,178
Axle lubricator, H. Augustine.....	305,239
Axle, vehicle, W. F. McNutt.....	305,144
Bag hinge stay, telescopic, C. Reinisch.....	305,276
Baling press, W. A. Laidlaw.....	305,187
Baling press, A. Wicker.....	305,211
Barium sulphate, process of and apparatus for treating, Page & Krause.....	305,318
Barrels, guard head for, G. H. & F. O. Kniffon.....	305,079
Battery. See Electric battery.	
Bed bottom, T. E. O'Brien.....	305,272
Bed guard, T. D. Smith.....	305,105
Bedstead, folding, F. E. Muller.....	305,248
Bell, call, Comstock & Buxton.....	305,341
Bending rails, etc., machine for, J. Abbott.....	305,375
Billiard cues, machine for trimming the ends of, J. S. Gold.....	305,301
Bit. See Bridle bit.	
Bitters, stomach, I. Cooper.....	305,243
Blast furnace top, Kennedy & Scott.....	305,077
Blast machine, sand, King & Maw.....	305,261
Blood, instrument for transfusion of, E. E. Allen.....	305,327
Bobbin winders, thread roll pin for, C. D. Austin.....	305,291
Boller. See Steam boiler.	
Bookcase, revolving, D. C. McMartin.....	305,085
Box. See Cock box. Journal box. Packing and show box.	
Box lock, W. Clark.....	305,048
Bottle stopper, W. Werts.....	305,293
Brace. See Rail brace.	
Bracelet, T. C. Hudson.....	305,257
Bracket. See Coffin bracket.	
Brake. See Car brake.	
Bread, making, J. D. Cox.....	305,331
Bridge gate, draw, G. A. Johnson.....	305,132
Bridle bit, H. T. Richmond.....	305,151
Brush handle attachment, G. J. Cline.....	305,329
Buckle, J. F. Bartlett.....	305,235
Buildings, corrugated ridge capping for, W. H. & B. F. Powers.....	305,086
Bustle, H. O. Canfield.....	305,045
Button and buttonhole marking machine, Hatfield & Sorge, Jr.....	305,126
Button fastening attachment, E. O. Ely.....	305,299
Buttonhole cutter, C. Dickenson.....	305,223
Cable roads, grip releasing device for, J. T. Cooney.....	305,169
Can. See Oil can. Packing can.	
Candy pail and show case, combined, J. Linted.....	305,346
Car brake, C. E. Corlies.....	305,245
Car coupling, D. R. Covenhoven.....	305,230
Car coupling, J. H. Dunn.....	305,173
Car coupling, O. E. Long.....	305,189
Car coupling, W. Metcalf.....	305,270
Car coupling, W. H. Phillips.....	305,149
Car coupling, D. H. Sherman.....	305,278
Car, safety, F. D. Knight.....	305,239
Car, safety railway, Maron & Bohm.....	305,143
Car seat, reversible, J. Leeman.....	305,231
Car seats, head rest for, H. W. Fackrell.....	305,248
Car starter, B. C. Poole.....	305,274
Cars, sand box for railway, H. W. Jordan et al.....	305,076
Carding machines, top flat stripping mechanism for, A. Falls.....	305,200
Carpet sweeper, J. M. McClain.....	305,139
Carriage, child's, V. Doane, Jr.....	305,298



Case. See Book case.	365,125	Latch, M. S. Thornd.	365,381	Soldering machine, can cap, E. Norton.	365,336
Chain, drive, M. Garland.	365,125	Latch operating device, A. H. Calkins.	365,386	Soldering tool, H. Brach.	365,390
Chain, ornamental, S. O. Hargreaves.	365,125	Light. See Locomotive headlight. Vault light.		Spark arrester, F. S. Bragg.	365,324
Chair. See convertible chair.		Lock. See Box lock. Combination lock. Motor lock. Nut lock. Seal lock.		Spark arrester for smokestacks, M. M. Wilson.	365,314
Chair, D. Snyder.	365,305	Lock, S. Simson.	365,382	Spectacle frame, J. L. Newell.	365,080
Cider, preserving, J. C. Mott.	365,148	Lock for bolts of pistons, J. & J. Wormald, Jr.	365,215	Spinning frames, roving guide for, F. A. Thomas.	365,380
Cigar perforator, F. C. Gudebrod.	365,305	Locomotive headlight, L. A. & C. L. Williams.	365,112	Spinning machines, yarn separating device for, G. E. Taft.	365,155
Cinder escape and draught regulator, F. S. Bragg.	365,235	Loom, circular, R. Sauter.	365,101	Spring. See Vehicle spring.	
Clamps to strips, machine for forming and attaching, Gardner & Loveland.	365,251	Loom shuttle, C. Widmer.	365,111	Station indicator and calendar, F. C. Jones.	365,154
Closet. See Dry closet.		Looms, shuttle operating mechanism for circular.		Steam boiler, E. G. Durant et al.	365,173
Clothes line support, Palmer & Carter.	365,195	Winckler & Heilmann.	365,216	Steam boiler, M. Mahony.	365,141
Clothes rack, T. H. Kulam.	365,090	Lounge, A. C. Abramson.	365,325	Steam engines, oil trap for, F. F. Ide.	365,259
Coal binder, Oberkay & Fischer.	365,271	Lubricator. See Axle lubricator.		Steam generating furnace, W. Gerkhardt.	365,253
Cock box, stop, C. F. Bingham.	365,293	Marker, corn row, Andrew & Vendrick.	365,039	Steam or hot water generator, R. J. Malcolm.	365,347
Coffee roaster, J. C. Salzgeber.	365,321	Marking wheel for transferring patterns, W. Heidenhain.	365,129	Stencil plates, die for cutting, J. L. Haberling.	365,095
Coffin bracket, adjustable, C. E. McLaughlin.	365,328	Measure, shoemaker's, A. S. Adler.	365,221	Stereoscope, G. D. Horton.	365,206
Combination lock, B. Fry.	365,177	Meat cutter, G. H. Stallman.	365,205	Stirrup, W. S. Cardell.	365,228
Combination lock, J. G. O'Neill.	365,177	Meter. See Water meter.		Stopper. See Bottle stopper.	
Condenser, W. Craik.	365,119	Milk, centrifugal apparatus for testing, G. De Laval.	365,130	Stove, cooking, J. A. Price.	365,349
Convertible chair, Lawrence & Batchelder.	365,244	Mill. See Rice mill. Rolling mill.		Stovepipe attachment for flues, A. M. Mealey.	365,145
Coverer, J. M. Dodge.	365,171	Mirror, P. Hufeland.	365,183	Stud and necktie holder, collar, D. Stone.	365,307
Cotton openers, dust trunk cleaner for, H. W. Fairbanks.	365,175	Mirror, F. W. Levering.	365,254	Stump puller, J. H. Schindly.	365,304
Cotton picking and cleaning machinery, W. H. Goldsmith.	365,125	Mould. See Pipe mould.		Suspension device, J. A. Harris.	365,347
Coupling. See Car coupling. Rod coupling. Thill coupling.		Mop head, F. L. Whittemore.	365,287	Tablet, interchangeable account, J. G. Mark.	365,084
Cultivator attachment, D. M. Ditto.	365,055	Mop wringer, J. F. Chase.	365,107	Tank. See Water closet tank.	
Cultivator, cotton, C. N. Hutchins.	365,055	Mortising machine, A. L. Grinnell.	365,065	Tea or coffee pot, Beach & Babbitt.	365,227
Current motor, H. Kessler.	365,123	Motor. See Current motor.		Telegraph, printing, S. V. Esick.	365,059
Curtain pole and button, F. C. Schaefer.	365,308	Multi-cylinder engine, A. D. Linn.	365,081	Telegraphy, automatic, C. Selden.	365,108
Cutter. See Battonhole cutter. Fuse cutter. Glass tube cutter. Meat cutter. Paper cutter.		Musical instruments, coupler for, W. D. Parker.	365,092	Temperature alarm system, A. E. Morrison.	365,089
Damper, J. W. Yates.	365,219	Nail, machine for and method of making double pointed wire, G. Doolittle.	365,121	Thermometer, G. B. St. John.	365,354
Dental chair, lowering mechanism for, L. Stuck.	365,022	Nut lock, Campbell & Hestler.	365,165	Thill coupling, F. R. Crumbaker.	365,052
Dental engine, H. C. Register.	365,028	Nut lock, C. S. Wenger.	365,295	Thill coupling, D. A. Johnson.	365,181
Desk and type writer cabinet, combined, W. H. Porter.	365,275	Nuts and washers, machine for manufacturing, S. Brightmore.	365,328	Tie. See Railway tie. Railway tie.	
Domestic press, J. S. Bird.	365,292	Nutshell cutting machine, C. Pecht.	365,138	Tie for ceilings and floors of buildings, J. H. Bright.	365,295
Door check, F. W. Andrews.	365,088	Odometer, H. O. Brooks.	365,043	Tire bolt holder, J. C. Markam.	365,142
Door check, W. S. Barlow.	365,224	Oil can, W. W. Hills.	365,130	Toy, spring, J. M. Highard.	365,201
Dredger, H. H. Lynch.	365,140	Oil can, siphon, C. N. Tyler.	365,157	Track gauge, automatic, D. Willard.	365,113
Dress form, C. H. Griffin.	365,302	Oil, automatic, J. T. Smith.	365,158	Train order catcher, R. J. Mickey.	365,314
Dress shields, die for making seams, A. J. Hirsch.	365,070	Oil, for car axles, J. Gibbons.	365,063	Trammel, A. Heiron.	365,181
Drier. See Fruit drier.		Ore concentrator, G. D. Stonestreet.	365,279	Trap, C. J. Erikson.	365,098
Drill. See Grain drill.		Oscillating engine, S. Maltby.	365,297	Trolley track, L. Coburn.	365,340
Drill stock, ratchet, C. H. Wilmoth.	365,214	Packing and show box, J. W. De Graff.	365,245	Truck for electric railways, guide, B. F. Hamilton.	365,389
Dry closet, L. B. Robb.	365,202	Packing apparatus, F. Wolf.	365,217	Truck for electric railways, swivel, B. F. Hamilton.	365,340
Ear and neck protector, L. Friedman.	365,061	Packing can, H. R. Gillingham.	365,254	Tubes, device for reducing the ends of, R. O. Daniels.	365,053
Electric battery, P. Germain.	365,339	Pantaloons, H. T. Caillet.	365,296	Umbrella support, D. E. Tillman.	365,282
Elastic compound, rubber covered, H. W. Libbey.	365,137	Paper box machine, H. A. House.	365,072	Valve, balanced, J. Lewis.	365,185
Electric currents, apparatus for transforming, L. Boltmann.	365,116	Paper boxes, machine for making bands for, J. Godfrey.	365,124	Valve, elastic balance, J. Lewis.	365,185
Elevator lock, T. F. Morris.	365,088	Paper pulp, etc., suspended in liquids, separating apparatus for, R. Kron.	365,243	Valve mechanism for water mains, electric, G. B. Bassett.	365,040
Engine. See Dental engine. Multi-cylinder engine. Oscillating engine.		Paper stock, apparatus for treating vegetable substances for making, A. Chambers.	365,105	Valve, rotary, J. L. Mitchell.	365,315
Envelope, letter, G. L. Jaeger.	365,330	Paper, waxing, C. A. Wilkinson.	365,213	Valve, thermal, J. Hurt.	365,258
Eraser, blackboard, J. Travis.	365,336	Pen holder, W. G. Ingram.	365,307	Vault covering, illuminating tiling, etc., T. Hyatt.	365,306
Extracts, process of and apparatus for clarifying, A. Morand.	365,087	Pen holder, M. I. Rodriguez.	365,320	Vault light, P. Herzer.	365,308
Feed water purifier, K. A. Petzold.	365,035	Pick and shovel, combined, A. H. Storey.	365,159	Vehicle, spring, H. C. Swan.	365,325
Fence machine, E. S. Plackard.	365,150	Pillow sham holder, T. Van Duser.	365,159	Vehicle wheel, J. Fraser.	365,122
Fence machine, wire, L. C. Lowden.	365,112	Pin. See Safety pin.		Velocepede, T. B. Jeffery.	365,074
Fence post, T. F. Lichart.	365,039	Pipes, coupling for joining, E. E. Hendrick.	365,085	Velocepede, F. D. Owen.	365,091
Fifth wheel, W. C. Engel.	365,174	Pipes, means for making curved, J. A. Whitney.	365,170	Vessels, construction of, T. J. Hanlon.	365,180
Filtering plate, compound, J. Kroeg.	365,134	Pipe mould, W. A. Erick.	365,175	Vise, J. Kenyon et al.	365,185
File, making, C. M. Fairbanks.	365,249	Piston, horizontal, H. Bee.	365,102	Vulcanizing apparatus, W. B. Mann.	365,083
Fire escape, B. Belcher.	365,240	Planter, corn, C. A. Boertercher.	365,229	Wad binding machine, A. Dickerman.	365,054
Fire extinguisher for car heaters, S. P. Canfield.	365,227	Planter, cotton, J. W. Bartlett.	365,041	Wagon, dumping, J. M. Blake.	365,233
Flambard, Vanhook & States.	365,294	Planters and other machines, adjustable driving gear for corn, P. J. Lawton.	365,188	Waldstans, attaching elastic straps to, E. A. Todd.	365,388
Frame. See Spectacle frame.		Planters, feed for cotton, C. W. Oldham.	365,195	Washing compound, J. K. McWhorter.	365,399
Fruit drier, C. Faltzinger.	365,319	Plow, Turley & Bryant.	365,156	Washing machine, M. V. B. Watson.	365,310
Furnace. See Hot air furnace. Smoke consuming furnace. Steam generating furnace.		Plow, R. W. Whitehurst.	365,156	Water closet tank, J. Collett.	365,049
Furnace, A. J. Holden.	365,071	Plow, double shovel, F. C. Geiger.	365,222	Water meter, piston, F. L. Sylvester.	365,323
Furniture, rocking, A. G. Wicker.	365,248	Plow, side hill, C. Anderson.	365,162	Wheel. See Fifth wheel. Marking wheel. Saw wheel. Vehicle wheel.	
Furniture, wall protecting attachment for, F. Harwood.	365,235	Pneumatic cabinet, W. J. Harris.	365,167	Wood turning machine, A. Schuch.	365,377
Fuse cutter, cap setter, and inserter, combined, C. D. Hale.	365,170	Pocketbooks, satchels, etc., frame for, L. B. Frahar.	365,300	Wringer. See Mop wringer.	
Gauge. See Track gauge.		Pocket knife, G. W. Miller.	365,085		
Galley, G. E. Jones.	365,309	Police man's club and making the same, E. D. Bean.	365,288		
Gas, apparatus for manufacturing, B. Brasile.	365,294	Post. See Fence post.			
Gas generators, acid chamber for, H. Hoff.	365,254	Post. See Tea or coffee pot.			
Gels. See Bridge gate.		Press. See Baling press. Domestic press.			
Generator. See Steam or hot water generator.		Presses, automatic brake for power, J. H. Clapp.	365,047		
Glass tube cutter, L. P. Lindgren.	365,190	Printing machine, chromatic, F. H. Ludington.	365,113		
Glasser's diamond tool, A. T. Duncan.	365,087	Printing machines, feed guide for, J. T. Hawkins.	365,127		
Grain binders, cord tying mechanism for, W. Butterfield.	365,044	Printing machines, web feeding mechanism for, L. C. Crowell.	365,051		
Grain binners, cord tying bill for, R. H. Corey.	365,050	Printing shell, O. J. Smith.	365,354		
Grain cleaning machine, A. Laidlaw.	365,080	Protector. See Ear and neck protector.			
Grain drill, L. E. Waterman.	365,169	Puller. See Stump puller.			
Guard. See Bed guard.		Rack. See Clothes rack.			
Hammer, tack, L. H. Hoover.	365,265	Rail brace, C. Alkins.	365,222		
Harrow, S. H. Chadwick.	365,046	Railway rail tie and fastening, A. Roelofs.	365,260		
Harrow, D. W. Shores.	365,104	Railway signal, electric, M. W. Long.	365,245		
Harvester platforms, clearing attachment for, D. H. Baisant.	365,097	Railway tie, G. De Beaulieu.	365,109		
Harvesting machine, W. N. Whiteley.	365,124	Railways, triplex motor for street, B. C. Poles.	365,273		
Hat wire, H. H. Kellner.	365,185	Railways, with means of insulating the rails, tramway for elevated electric, B. F. Hamilton.	365,341		
Hay loader, W. S. Nichols.	365,124	Rake. See Hay rake.			
Hay rake and gathering machine, A. L. Courtright.	365,118	Reflector, lamp, R. E. Williams.	365,215		
Hay rake and loader, W. H. Lyon.	365,082	Registers, heat deflector for, H. P. Klein.	365,078		
Hay stacker, D. B. Craig.	365,122	Regulator. See Heat regulator.			
Hay stacking device, O. H. King.	365,203	Rice mill, J. A. Lockfaw.	365,191		
Heat regulator, E. Zickwolf.	365,220	Road making machine, F. T. Lomont.	365,138		
Hinge, lock, J. Wolf.	365,160	Roaster. See Coffee roaster.			
Hoe, planting, W. & L. H. Trubee.	365,108	Rod, machine for upsetting collars on, C. O. Winder.	365,212		
Hoisting machine, W. B. Thatcher.	365,107	Roller. See Land roller.			
Holder. See Pen holder. Pillow sham holder. Tire bolt holder.		Rolling mill, H. Back.	365,100		
Hot air furnace, L. J. Mueller.	365,198	Roof, sheet metal, A. Wrightman.	365,220		
Hub, wheel, J. M. Sweet.	365,100	Rope making machine, E. E. Pierce.	365,094		
Ice chute, J. Hall.	365,259	Safe, etc., compound welded plate, for burglar proof, J. Farrel.	365,300		
Indicator. See Station indicator.		Safety pin, J. Jenkins.	365,075		
Insulating material, composition of matter for, J. B. Williams (r).	365,170	Saw level and set square, J. Beaulieu.	365,163		
Iron. See Bed iron.		Saw sharpening machine, S. A. Gould.	365,267		
Joint. See Sheet metal joint.		Saw wheel, band, D. K. Allington.	365,037		
Journal box, W. J. Perkins.	365,159	Scale beam latches, device for disengaging, E. O. Denning.	365,170		
Journal box and lubricator, A. Blegle.	365,241	Scale, coin operated electrical weighing, Smith & Washburn.	365,263		
Key, F. A. Gurney.	365,304	School seat and desk, W. P. Connor.	365,297		
Kitchen cabinet, V. K. Wigginton.	365,289	Seal lock, M. F. Berry.	365,221		
Knife. See Pocket knife.		Seal lock, C. V. Boughton.	365,137		
Knitting machine, Corvill & Cram.	365,244	Seat. See Car seat. School seat.			
Ladder, fire, H. T. Hayes.	365,128	Shaft support, T. A. Knox.	365,310		
Label, bottle, E. L. Moodie.	365,146	Sheet metal joint, J. G. Battelle.	365,043		
Lamp attachment, J. W. Bulger.	365,164	Shutter worker, J. Wayland.	365,267		
Lamp, gas, L. G. Francis.	365,286	Signal. See Railway signal.			
Lamp, incandescent electric, J. Smith.	365,181	Skirt facings, woven fabric for, L. Moschowitz.	365,147		
Lamp socket and cut-out, incandescent, Lamp & Wightman.	365,180	Slate, folding tracing, W. D. Hoyer.	365,182		
Lamp socket and cut-out, incandescent, Wightman & Lamp.	365,180	Sled, A. Wolf.	365,161		
Lamp, street car, C. E. Garay.	365,092	Smoke consuming furnace, J. W. Hubber.	365,042		
Land roller and old crusher, combined, F. Twick.	365,150	Snow plow, A. E. Dietz.	365,055		
Lat, Stevens & Smith.	365,154	Snow plow, H. Pangborn.	365,197		
		Sofa or divan, reclining, W. J. Maddox.	365,205		

## Advertisements.

Inside Page, each insertion --- 75 cents a line.  
Back Page, each insertion --- \$1.00 a line.  
The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head advertisement at the same rate per agate line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

**SEBASTIAN, MAY & CO'S**  
Improved Screw Cutting  
**LATHES** Foot & Power \$60.  
Drill Presses, Chucks, Drills, Dogs, and machinists' and amateurs' outfit. Lathes on trial. Catalogues mailed on application.  
165 W. 2d St., Cincinnati, O.

**SUPERIOR**  
Stationary Engines  
with Plain and Automatic Cut-off. Vertical and Horizontal.  
Penna. Diamond Drill Co., Birdsboro, Pa.

**FIRE-BRICK.—BY R. A. COOK, A.M.**  
An interesting description of the mining of fire clay and the manufacture of fire brick at Mt. Savage, Maryland where is located one of the largest establishments in the country devoted to this industry. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 5335. Price 10 cents. To be had at this office and from all newsdealers.

**J. RAYNER, MAHOGANY**  
Cabinet Woods all Thickness.  
Foot Houston Street, E. R., 275 & 289 East 20th Street, NEW YORK. CHICAGO, ILL.

**ON STEAM BOILERS.—A LECTURE**  
by J. M. Allen, delivered in the Sibley College course. The steam boiler, its construction and management. Different types of boilers. Material, Methods of riveting. Fractures, boiler explosions. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 5335. Price 10 cents. To be had at this office and from all newsdealers.

**Syracuse Malleable Iron Works**  
Corrugated Copper Gaskets.  
(patented) used in place of rubber or other destructible packings for connecting flange pipes, cylinder heads, steam chests, etc. This gasket is not injured by steam, oil, or acid solutions. U. S. Mineral Wool Company, 22 Cortlandt St., N. Y.

**ELECTRICAL.** Edward P. Thompson, Solicitor  
Street, N. Y. Write for testimonials and instructions.  
**EXCELLENT PLAIN COPIES of anything written or drawn with any Pen (or Type Writer) by the Patent**  
**AUTOCOPYIST** Only equalled by Lithography. Specimens Free.  
AUTOCOPYIST CO., 155 William Street, New York.

**THE COPYING PAD.—HOW TO MAKE**  
and how to use, with an engraving. Practical directions how to prepare the gelatine pad, and also the outline by which the copies are made: how to apply the written letter to the pad; how to take off copies of the letter. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 438. Price 10 cents. For sale at this office and by all newsdealers in all parts of the country.

**THE CHEAPEST AND BEST**  
**PHOTO ENGRAVING CO.**  
67 PARK PLACE, NEW YORK  
ENGRAVING FOR ALL ILLUSTRATIVE AND ADVERTISING PURPOSES

**SOMETHING NEW!** The Cyclone Carpet Sweeper. Just out, and is the best sweeper invented. It is for sale by state rights, or I will sell a half interest in the United States. Address JOHN M. McCLAIN, Catlin, Colorado.

**2d HAND MACHINERY** Lists sent.  
N. Y. Machinery Depot,  
Bridge Street No. 16,  
Frankfort Street, N. Y.

**MALLEABLE** AND FINE GRAY IRON ALLOY STEEL  
CASTINGS FROM SPECIAL PATTERNS  
THOMAS DEVLIN & CO. LONDON & AMSTERDAM

**TELESCOPIC OBJECTIVES AND MIRRORS.** Their preparation and testing. By H. Grubb, F. R. S. An interesting description of the processes now employed in the construction of telescopic objectives, refracted with a short history of the manufacture of glass. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 5428 and 5429. Price, 10 cents each. To be obtained at this office or from any newsdealer.

**PERFECT**  
**NEWSPAPER FILE**  
The Koch Patent File, for preserving newspapers, magazines, and pamphlets, has been recently improved and price reduced. Subscribers to the SCIENTIFIC AMERICAN and SCIENTIFIC AMERICAN SUPPLEMENT can be supplied for the low price of \$1.50 by mail, or \$1.25 at the office of this paper. Heavy board sides; inscription "SCIENTIFIC AMERICAN" in gilt. Necessary for every one who wishes to preserve the paper.  
Address **MUNN & CO.,** Publishers SCIENTIFIC AMERICAN.

**THE USE OF TORPEDOES IN WAR.**  
A paper by Commander E. P. Gallert, U.S.N., giving a clear presentation of the present state of efficiency of the torpedo, the degree of perfection that it has now reached, and describing the kinds which are in ordinary use in all naval services. With 5 plates, containing many figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 5346 and 5347. Ten cents each. To be had at this office and from all newsdealers.

**THE ONLY PRACTICAL**  
**ELECTRIC MOTORS**  
ON FAMILY-DRIVING MACHINES  
H. S. LITTLE-DYNAMO CO. PHILA.  
1224 ARCH ST.

A printed copy of the specification and drawing of any patent in the foregoing list, also of any patent issued since 1865, will be furnished from this office for 35 cents. In ordering please state the number and date of the patent desired, and remit to Munn & Co., 361 Broadway, New York. We also furnish copies of patents granted prior to 1865; but at increased cost, as the specifications, not being printed, must be copied by hand.

Canadian Patents may now be obtained by the inventors for any of the inventions named in the foregoing list, provided they are simple, at a cost of \$40 each. If complicated the cost will be a little more. For full instructions address Munn & Co., 361 Broadway, New York. Other foreign patents may also be obtained.



# IMPORTANT TO METALLURGISTS, MINERALOGISTS, MINERS, ASSAYERS, CHEMISTS, ETC., ETC.

We have just compiled a very complete List of Recent and Standard Works on the above subjects, which we will be glad to send free by mail, postage paid, to any one who will apply.

Also a New Catalogue of Books on Electro-Metallurgy, Moulding, Founding, Pattern Making, and Metal Working, which will be sent free upon application.

Our Catalogue of Practical and Scientific Books, 96 pages, 20, and our other Catalogues and Circulars, the whole covering every branch of Science applied to the Arts, sent free, and free of postage, to any one in any part of the world who will furnish his address.

**HENRY CAREY BAIRD & CO.,**

INDUSTRIAL PUBLISHERS, BOOKSELLERS & IMPORTERS

810 Walnut Street, Philadelphia, Pa., U. S. A.

## SCIENTIFIC BOOK CATALOGUE, JUST PUBLISHED.

Our new catalogue containing over 100 pages, including works on more than fifty different subjects. Will be mailed free to any address on application.

MUNN & CO., Publishers Scientific American,  
361 Broadway, New York.



## OF THE Scientific American FOR 1887.

The Most Popular Scientific Paper in the World.  
Only \$3.00 a Year, including Postage. Weekly.  
52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteen pages of useful information and a large number of original engravings of new inventions and discoveries, representing Engineering Works, Steam Machinery, New Inventions, Novelties in Mechanics, Manufactures, Chemistry, Electricity, Telegraphy, Photography, Architecture, Agriculture, Horticulture, Natural History, etc.

All classes of Readers find in the SCIENTIFIC AMERICAN a popular resume of the best scientific information of the day; and it is the aim of the publishers to present it in an attractive form, avoiding as much as possible abstruse terms. To every intelligent mind, this journal affords a constant supply of instructive reading. It is promotive of knowledge and progress in every community where it circulates.

**Terms of Subscription.**—One copy of the SCIENTIFIC AMERICAN will be sent for one year—52 numbers—postage prepaid, to any subscriber in the United States or Canada, on receipt of three dollars by the publishers; six months, \$1.50; three months, \$1.00.

**Clubs.**—One extra copy of the SCIENTIFIC AMERICAN will be supplied gratis for every club of five subscribers at \$3.00 each; additional copies at same proportionate rate.

The safest way to remit is by Postal Order, Draft, or Express Money Order. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, seldom goes astray, but is at the sender's risk. Address all letters and make all orders, drafts, etc., payable to

**MUNN & CO.,**  
361 Broadway, New York.

## Scientific American Supplement.

This is a separate and distinct publication from THE SCIENTIFIC AMERICAN, but is uniform therewith in size, every number containing sixteen large pages. THE SCIENTIFIC AMERICAN SUPPLEMENT is published weekly, and includes a very wide range of contents. It presents the most recent papers by eminent writers in all the principal departments of Science and the Useful Arts, embracing Biology, Geology, Mineralogy, Natural History, Geography, Archaeology, Astronomy, Chemistry, Electricity, Light, Heat, Mechanical Engineering, Steam and Railway Engineering, Mining, Ship Building, Marine Engineering, Photography, Technology, Manufacturing Industries, Sanitary Engineering, Agriculture, Horticulture, Domestic Economy, Biography, Medicine, etc. A vast amount of fresh and valuable information pertaining to these and allied subjects is given, the whole profusely illustrated with engravings.

The most important Engineering Works, Mechanisms, and Manufactures at home and abroad are represented and described in the SUPPLEMENT.

Price for the SUPPLEMENT for the United States and Canada, \$5.00 a year, or one copy of the SCIENTIFIC AMERICAN and one copy of the SUPPLEMENT, both mailed for one year for \$7.00. Address and remit by postal order, express money order, or check.

**MUNN & CO., 361 Broadway, N. Y.,**  
Publishers SCIENTIFIC AMERICAN.


**To Foreign Subscribers.**—Under the facilities of the Postal Union, the SCIENTIFIC AMERICAN is now sent by post direct from New York, with regularity, to subscribers in Great Britain, India, Australia, and all other British colonies; to France, Austria, Belgium, Germany, Russia, and all other European States; Japan, Brazil, Mexico, and all States of Central and South America. Terms, when sent to foreign countries, Canada excepted, \$4.00, for SCIENTIFIC AMERICAN, one year; \$6.00, gold for both SCIENTIFIC AMERICAN and SUPPLEMENT for one year. This includes postage, which we pay. Remit by postal or express money order, or draft to order of

**MUNN & CO., 361 Broadway, New York.**

## CURE FOR THE DEAF

FRICK'S PATENT IMPROVED CONDUIT EAR DRUMS PERFECTLY restore the hearing, and perform the work of the natural drum. Invisible, comfortable and always in position. All conversation and even whispers heard distinctly. Send for illustrated book with testimonials, FREE. Address or call on F. FRICK, 863 Broadway, New York. Mention this paper.

**PILES.** Instant relief. Final cure and never returns. No incision. Neither knife, purge, salve or suppository. Liver, kidney and all bowel troubles—especially constipation—cured by the use of Dr. J. H. REEVES' Pile Remedy. Address, by mail, J. H. REEVES, 10 Nassau St., N. Y.



## LIGHT DRAFT STEAM LAUNCHES. COAL AND WOOD BURNING.

Small Marine and High Speed Engines, also Patent Steel Tubular Boilers. Patent Automatic Adjustable SEAG.

MANUFACTURED BY  
**H. B. WILLIAMS & CO.,** Rochester, N. Y., U. S. A.

## STEAM ROAD ROLLERS

Manufactured by  
Foundry and Machine Dep't,  
Harrisburgh, Pa.

## Shafting and Gearing. Textile Machinery, ELEVATORS, ETC.

**THOS. WOOD & CO.**  
22d and Wood Sts.,  
Philadelphia, Pa.

**PROPULSION OF STREET CARS.**—A paper by A. W. Wright, in which an endeavor is made to solve the problem as to the amount of power required to start a street car and keep it in motion under average conditions. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 533. Price 10 cents. To be had at this office and from all newsdealers.



**WELLS BROS. & CO., GREENFIELD, MASS.**  
MANUFACTURERS OF  
Screw Cutting Machinery and Tools for Machinists,  
Carriage Makers, and Blacksmiths' Use.

**STEEL GUNS, GUN METAL, GUN-  
powder, etc.** A paper by G. W. Sumner, Commander,  
U. S. N., treating of the relative merits of different materials used in gun making, describing the peculiarities of the Whitworth system of artillery, and discussing the subject of slow-burning gunpowder. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 533. Price 10 cents. To be had at this office and from all newsdealers.

**NOTICE to Users of Steam Pumps.**  
We have received following letter in regard to one of our No. 5 "L" (80) Steam Jet Pumps elevating 14 inch pipe of water more than 50 feet high:  
"LANSE, MICH., Feb. 24, 1887.  
"VAN DUZEN & TIFT, Cincinnati, O.:  
"Money could not buy the Jet of us unless another could be had. I would not give your No. 5 "L" for a \$700 pump, equal distance to raise."  
"N. A. Litchfield, Supt. Mich. State Co."  
We make Ten Sizes of these Pumps. Prices \$1 to \$75. Capacities 10 to 50,000 gallons per hour. State for what purpose wanted and send for Catalogue of "Pumps."  
VAN DUZEN & TIFT, Cincinnati, O.

**ELECTRIC CONVEYORS.**—DESCRIPTION of two ingenious systems for the electric carriage of small packages. Illustrated with 15 engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 533. Price 10 cents. To be had at this office and from all newsdealers.

**VOLNEY W. MASON & CO.,**  
FRICTION PULLEYS CLUTCHES AND ELEVATORS  
PROVIDENCE, R. I.



## ROCK BREAKERS AND ORE CRUSHERS.

We manufacture and supply at short notice and lowest rates, Stone and Ore Crushers, containing the invention described in Letters Patent issued to Eli W. Blake, June 15th, 1886, together with NEW AND VALUABLE IMPROVEMENTS, for which Letters Patent were granted May 11th and July 25th, 1887, to Mr. S. L. Marsden. All Crushers supplied by us are constructed under the superintendence of Mr. Marsden, who, for the past twenty years, has been connected with the manufacture of Blake Crushers in this country and England.

**FARREL FOUNDRY AND MACHINE CO.,** Manufact., Ansonia, Conn.  
**COPELAND & BACON, Agents, NEW YORK.**

## OTTO GAS ENGINE AGENCY, NEW YORK.

**A. O. MANNING & CO., 47 Dey Street**

**Removes on May 1st to 18 VESEY STREET.**

**CLARK'S NOISELESS RUBBER WHEELS**  
No more Splintered Floors.  
Different Styles. Catalogue Free.  
**GEO. P. CLARK,**  
Box 1, Windsor Locks, Ct.

**HOW TO GRAFT.—A VALUABLE PAPER,** giving complete directions for making various kinds of grafts in fruit trees.—Cleft grafting, slip grafting, bear's mouth grafting, wired grafting, side grafting, whip grafting, saddle grafting, tongue grafting, split grafting, crown grafting, Grafting wax. Wax cloth. With 11 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 533. Price 10 cents. To be had at this office and from all newsdealers.



**ICE-HOUSE AND REFRIGERATOR.**  
Directions and Dimensions for construction, with one illustration of construction, showing the method of season to season. The air is kept dry and pure throughout the year at a temperature of from 34° to 38°. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 116. Price 10 cents. To be had at this office and from all newsdealers.

**VALUABLE PATENT FOR SALE.**  
For particulars write to the ADAMSON CO. (Agents for Selling Patents), Muncie, Indiana.

**PARTNER WANTED, OR FOR SALE.**—A newly patented appliance in Laundry Irons, automatically announcing to ear and eye the iron is to have attained the heat required for their proper use, very plain and simple, self insurance, profile large. Model and information at Heupel & Co., 30 Bond Street, New York City.

**STEAM PUMPS** for Hot or Cold, Fresh or Salt Water; for Oils, Naphtha, Tar; for Cane Juice, Liquors, Syrups, Scum; for Ammonia, Alkalies, Extracts, Acids; for Thick, Viscous or Foul Liquids, etc. Vacuum Pumps of the highest efficiency. Filter Press Pumps. Air, Gas and Acid Blowers. Air Compressors, Etc.  
BUILT BY GUILD & GARRISON, Brooklyn, N. Y.

**FOR SALE.** Newly patented device to automatically and instantly Stop Pumping, particularly hot-air engines, long sought after, wanted everywhere, construction simple and substantial, large saving in water and gas, device attached now and working perfectly. Heupel, 30 Bond St., New York City.

**New Catalogue of Valuable Papers** contained in SCIENTIFIC AMERICAN SUPPLEMENT, sent free of charge to any address.  
**MUNN & CO., 361 Broadway, N. Y.**

## ICE & REFRIGERATING




**MODEL and EXPERIMENTAL WORK SPECIALTY.**  
Send for Circulars,  
**C. E. Jones & Bro.**  
CINCINNATI, O.  
(Mention this Paper.)

**CAPILLARY TUBES, SPONTANEOUS**  
Motion in.—A paper by C. Dechamps upon the application of electricity to the study of the spontaneous oscillation of liquids in capillary tubes—the question being studied from a dynamic standpoint. With 10 engravings of apparatus and details. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 533. Price 10 cents. To be had at this office and from all newsdealers.

**GEO. W. MARBLE, Sole Manufacturer of the ACME WRENCH.**  
The best made, all steel, and warranted, 5 sizes.  
25 to 32 South Canal Street, Chicago, U. S. A.

## THE NEW CROTON AQUEDUCT.

Detailed description of the great aqueduct now being constructed to increase the water supply of New York City, and also of the great dam which it is proposed to build across the Croton River, at Quaker Bridge. With engravings and a map. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 533. Price 10 cents. To be had at this office and from all newsdealers.



**THE CURTIS RETURN STEAM TRAP.**  
For returning steam condensed under pressure automatically into the boiler, whether taken from above or below the boiler level, without loss or waste. Manufactured by  
**THE CURTIS REGULATOR CO.,**  
BOSTON, MASS.  
Send for Circular No. 19.

**ALCOHOL, SWEET POTATO.—AN** account of a new industry recently established at the Azores—that of the distillation of alcohol from raw sweet potatoes. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 532. Price 10 cents. To be had at this office and from all newsdealers.

**Water Wheels New and Second Hand**  
Address FLENNIKEN TURBINE CO., Dubuque, Iowa.

**WELL TOOLS.** Encyclopedia of 700 Engravings of WELL TOOLS, Diamond Drills and Lighting Hydraulic Wells, Book free, 25c. for mailing it. American Well Works, Aurora, Ill.

**CAPILLARY ATTRACTION.—AN** interesting paper by William Thomson, discussing the question whether the attraction between any particle of matter in one body and any particle of matter in another continues to vary inversely as the square of the distance, when the distance between the nearest points of the two bodies is diminished by various degrees. With 30 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 562 and 563. Price 10 cents each. To be had at this office and from all newsdealers.

**MACHINES.** York Patent. YORK MFG. CO., York, Pa.

## Proposals for Steel-cast Guns for the Navy.

NAVY DEPARTMENT.

WASHINGTON, D. C., June 23, 1887.

Under authority conferred by the act of Congress, approved March 3, 1887, making an appropriation "for the purchase and completion of three steel-cast, rough-bored and turned, six-inch, high-power rifle cannon, of domestic manufacture, one of which shall be of Bessemer steel, one of open-hearth steel, and one of crucible steel," sealed proposals from domestic manufacturers, to furnish the same, will be received at this Department until Tuesday, the second day of August, 1887, at 12 o'clock noon, at which time the proposals will be opened.

Proposals may be made either to furnish three completely finished six-inch, breech-loading, high-power rifle cannon, made from unforged castings, one of Bessemer steel, one of open-hearth steel, and one of crucible steel, or three unforged, rough-bored and turned castings for such cannon, of the same material, respectively, to be finished by the Department in accordance with the bidder's design.

Such finished guns or such castings must be in accordance with the specifications prepared in the Bureau of Ordnance, and each gun, when completed, must be capable of safely discharging projectiles weighing 100 pounds each, with a muzzle velocity of not less than 2,000 feet per second.

No gun or casting for a gun will be paid for until the gun "shall have been completed and have successfully stood the statutory test required by the act of July twenty-sixth, eighteen hundred and eighty-six," entitled "an act making appropriations for the naval service for the fiscal year ending June thirtieth, eighteen hundred and eighty-seven, and for other purposes."

Proposals may be made separately for one or more guns or for one or more castings as aforesaid, but no proposal will be considered unless accompanied by satisfactory evidence that the bidder controls a plant adequate to the production of the gun or guns, casting or castings, which he proposes to furnish.

Each successful bidder will be required to execute, within fifteen days after notice of award, a formal contract in accordance with his proposal, and to furnish a bond, with satisfactory sureties, in a penalty sum equal to fifteen per cent. of the amount of his bid, conditioned for the faithful performance of such contract.

Copies of the specifications, with blank forms of proposals, and all additional information desired, can be obtained on application to the Bureau of Ordnance, Navy Department.

All proposals must be in duplicate, inclosed in envelopes marked "Proposals for Steel-cast Cannon," and addressed to the Secretary of the Navy, Navy Department, Washington, D. C.

The right is reserved to waive defects in form and to reject any or all bids.

WILLIAM C. WHITNEY,

Secretary of the Navy.

## Proposals for Steel Gun Forgings for the Navy.

NAVY DEPARTMENT.

WASHINGTON, June 4, 1887.

Sealed proposals from domestic manufacturers of steel, to furnish ten sets of steel forgings for 6-inch R. L. rifle guns and one set of chain-hoops for a 10-inch R. L. rifle gun, all oil-treated, annealed, and in accordance with drawings and specifications prepared in the Bureau of Ordnance, will be received at the Navy Department until Wednesday, the 6th day of July, 1887, at 12 o'clock noon, at which time the proposals will be opened.

The kinds of forgings required and the estimated quantity of each, the aggregate being about sixty-five tons, are stated in blank forms of proposal, which, together with copies of said drawings and specifications, may be obtained on application to the Bureau of Ordnance, Navy Department.

Prices per ton of 2,240 pounds must be stated in the proposals, which must be made on forms furnished by the Department. Proposals will include, in addition to items embracing all the work required in the manufacture of the forgings as specified, separate items for tubes, jackets, and flange-hands to be rough-bored and turned by the Department. In case the Department shall find it advantageous to have that part of the work done at the Navy Yard, Washington, D. C., such forgings will be delivered by the contractor before roughing, the Department paying freight to and from the Navy Yard, and the rough-bored and turned forgings will be returned to the contractor, F. O. B. at his works.

The contract will be awarded for the forgings as a whole. No proposal for less than the whole will be entertained, nor will any proposal be considered unless accompanied by satisfactory evidence that the bidder is in possession of a plant adequate to the production and delivery of the required forgings. All forgings delivered under the contract must conform in material, manufacture, and quality to the aforesaid drawings and specifications, and must successfully pass the required inspection and tests.

The successful bidder will be required, within ten days after notice of award, to enter into a formal contract binding himself to deliver one set of gun forgings within sixty days from the date of the contract, and not less than one set every twenty-one days thereafter, and to complete the deliveries within nine months from the date of the contract. A bond with sufficient sureties in a penalty sum equal to fifteen per cent. of the total contract price must accompany the contract.

Blank forms of contract and all additional information desired can be obtained on application to the Bureau of Ordnance, Navy Department.

Each proposal must be accompanied by a certified check, payable to the order of the Secretary of the Navy, in an amount not less than five per cent. of the total amount of the bid. Checks of unsuccessful bidders will be returned within five days after the bids are opened. The check of the successful bidder will be returned when he shall have executed the formal contract and furnished the requisite bond; in case of his failure to comply with this stipulation, the check will become the property of the United States.

All proposals must be in duplicate, enclosed in envelopes marked "Proposals for Steel Gun Forgings," and addressed to the Secretary of the Navy, Navy Department, Washington, D. C.

The right is reserved to waive defects in form and to reject any or all bids.

WILLIAM C. WHITNEY,

Secretary of the Navy.

## Proposals for Iron, Floating Gate or Caisson.

NAVY DEPARTMENT.

WASHINGTON, D. C., June 5, 1887.

Sealed proposals, addressed to the Chief of the Bureau of Yards and Docks, Navy Department, Washington, D. C., indorsed "Proposals for Floating Gate," will be received at this Bureau by the undersigned until one o'clock, p. m., of Thursday, the thirtieth day of June, 1887, at which time and place the proposals will be opened in the presence of bidders for furnishing the necessary labor and material for the construction of an iron floating gate, or caisson, for the dry dock at the Navy Yard, Boston, Mass.

Plans of the floating gate, or caisson, and all attachments pertaining thereto, can be seen and copies of specifications and instruction to bidders obtained by applying to the Bureau of Yards and Docks, Navy Department, the Civil Engineer's office at the Navy Yard, Boston, Mass., or at Navy Pay Office, cor. Broadway and Chambers Street, Stewart Building, New York City.

The Bureau reserves the right to reject any or all bids that may not be deemed advantageous to the government. No proposal will be considered unless accompanied by the prescribed bond which forms a part of the same.

D. B. HARMONY,

Chief of Bureau.

## BARREL, KEQ, Hogshead, AND STAVE MACHINERY.

Over 50 varieties manufactured by  
**E. & B. Holmes,**  
BUFFALO, N. Y.

Truss Hoop Driving.

EDUCATION OF THE AMERICAN Citizen.—A lecture by Prof. R. H. Thurston on the theme: "How may we best aid in those mighty social movements and those tremendous political changes which mark the mighty progress of the race toward a better and a more prosperous future?" Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 524. Price 10 cents. To be had at this office and from all newsdealers.

STEEL WIRE OF EVERY DESCRIPTION. STEEL SPRINGS. NEW YORK.



## Advertisements.

Inside Page, each insertion --- 75 cents a line.  
Back Page each insertion --- \$1.00 a line.  
The above are charges per square line—about eight words per line. This notice shows the width of the line, and is set in single type. Engravings may bear advertisements at the same rate per square line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.



**FATENT JACKET KETTLES,**  
Plain or Porcelain Lined. Tested to 100 lb. pressure.  
Send for Lists.  
BLAND, BURE & CO.,  
614 and 616 Market St., Philadelphia, Pa.

**DROP FORGINGS**  
FINISHED TOOLS  
BILLINGS & SPENCER CO.

Any one can take good Photographs  
Outfits \$10. and upward.  
SEND FOR A COPY OF MODERN PHOTOGRAPHY  
AND OUR ILLUSTRATED CATALOGUE  
**ROCHESTER OPTICAL CO.**  
21 ADEPHY ST. ROCHESTER N.Y.

## FOREIGN PATENTS.

Their Cost Reduced.

The expenses attending the procuring of patents in most foreign countries having been considerably reduced the obstacle of cost is no longer in the way of a large proportion of our inventors patenting their inventions abroad.

**CANADA.**—The cost of a patent in Canada is even less than the cost of a United States patent, and the former includes the Provinces of Ontario, Quebec, New Brunswick, Nova Scotia, British Columbia, and Manitoba.

The number of our patentees who avail themselves of the cheap and easy method now offered for obtaining patents in Canada is very large, and is steadily increasing.

**ENGLAND.**—The new English law, which went into force on Jan. 1st, 1885, enables parties to secure patents in Great Britain on very moderate terms. A British patent includes England, Scotland, Wales, Ireland and the Channel Islands. Great Britain is the acknowledged financial and commercial center of the world, and her goods are sent to every quarter of the globe. A good invention is likely to realize as much for the patentee in England as his United States patent produces for him at home, and the small cost now renders it possible for almost every inventor in this country to secure a patent in Great Britain, where his rights are as well protected as in the United States.

**OTHER COUNTRIES.**—Patents are also obtained on very reasonable terms in France, Belgium, Germany, Austria, Russia, Italy, Spain (the latter includes Cuba and all the other Spanish Colonies), Brazil, British India, Australia, and the other British Colonies.

An experience of forty years has enabled the publishers of THE SCIENTIFIC AMERICAN to establish competent and trustworthy agencies in all the principal foreign countries, and it has always been their aim to have the business of their clients promptly and properly done and their interests faithfully guarded.

A pamphlet containing a synopsis of the patent laws of all countries, including the cost for each, and other information useful to persons contemplating the procuring of patents abroad, may be had on application to this office.

**MUNN & CO.,** Editors and Proprietors of THE SCIENTIFIC AMERICAN, cordially invite all persons desiring any information relative to patents, or the registry of trade-marks, in this country or abroad, to call at their offices, 361 Broadway. Examination of inventions, consultation, and advice free. Inquiries by mail promptly answered.

Address, **MUNN & CO.,**  
Publishers and Patent Solicitors,  
361 Broadway, New York.

BRANCH OFFICES: No. 632 and 634 F Street, Pacific Building, near 7th Street, Washington, D. C.

## PATENTS.

**MESSES. MUNN & CO.,** in connection with the publication of THE SCIENTIFIC AMERICAN, continue to examine inventions, and to act as Solicitors of Patents for Inventors.

In this line of business they have had forty-one years' experience, and now have unequalled facilities for the preparation of Patent Drawings, Specifications, and the prosecution of Applications for Patents in the United States, Canada, and Foreign Countries. Messrs. Munn & Co. also attend to the preparation of Caveats, Copyrights for Books, Labels, Reliefs, Assignments, and Reports on Infringements of Patents. All business entrusted to them is done with special care and promptness, on very reasonable terms.

A pamphlet sent free of charge, on application, containing full information about Patents and how to procure them; directions concerning Labels, Copyrights, Designs, Patents, Assignments, Infringements, Assignments, Rejected Cases, Hints on the Sale of Patents, etc.

We also send, free of charge, a Synopsis of Foreign Patent Laws, showing the cost and method of securing patents in all the principal countries of the world.

**MUNN & CO.,** Solicitors of Patents,  
361 Broadway, New York.

BRANCH OFFICES:—No. 632 and 634 F Street, Pacific Building, near 7th Street, Washington, D. C.




**DO NOT BUY** a Drill Chuck until you have seen the "Hartford." It is the strongest, best, and in now made in three sizes as follows:  
No. 6, holding from 9 to 14 in.  
No. 8, " " 14 to 20 " "  
No. 10, " " 20 to 30 " "  
Send for catalogue of every size and description.  
The Cushman Chuck Co., Hartford.

**THE INVENTION OF MACHINES.**  
A paper by Prof. Hale Shaw, pointing out what is necessary for the foundation of a science of the invention of machines, and showing what steps have already been taken in this direction. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 542. Price 10 cents. To be had at this office and from all newsdealers.

ESTABLISHED HALF A CENTURY.

**MARVIN'S**  
FIRE & BURGLAR  
**SAFES**

HAVE MANY PATENTED IMPROVEMENTS  
NOT FOUND IN OTHER MAKES  
THAT WILL WELL REPAY AN INVESTIGATION  
BY THOSE WHO DESIRE TO SECURE  
**THE BEST SAFE**  
**MARVIN SAFE CO.**  
NEW YORK, PHILADELPHIA,  
LONDON, ENGLAND.



**RUBBER BELTING, PACKING, HOSE,**  
AND ALL OTHER KINDS OF  
**RUBBER GOODS,**

FOR  
MECHANICAL AND MANUFACTURING PURPOSES.

The Largest and Most Extensive Manufacturers in America.

**THE GUTTA PERCHA AND RUBBER MFG. CO.**  
New York, Chicago, San Francisco, Toronto.

## SHAFTING, PULLEYS, HANGERS, AND GEARING.

Get estimates from Christopher Machine Co.,  
306 No. 4th Street, Phila., Pa., before ordering.

## USEFUL BOOKS.

Manufacturers, Agriculturists, Chemists, Engineers, Mechanics, Builders, men of leisure, and professional men, of all classes, need good books in the line of their respective callings. Our post office department permits the transmission of books through the mails at very small cost. A comprehensive catalogue of useful books by different authors, on more than fifty different subjects, has just been published for free circulation at the office of this paper. Subjects classified with names of author. Persons desiring a copy, have only to ask for it, and it will be mailed to them. Address,  
**MUNN & CO., 361 Broadway, New York.**



**FIRE AND WATER-PROOF BUILDING FELT,**  
FIRE-PROOF PAINTS, STEAM PACKINGS, BOILER COVERINGS, ETC.

Samples and descriptive Price List free by mail.  
**H. W. JOHNS MFG CO., ST. MAIDEN LANE, N. Y.**




**ROSE POLYTECHNIC INSTITUTE,**  
TERRE HAUTE, IND. | A School of Engineering.  
Well endowed, well equipped departments of Mechanical and Civil Engineering, Electricity, Chemistry and Drawing. Extensive Shops and Laboratories. For Catalogue, address T. C. MENDENHALL, Pres.



Mention this paper.

## VULCANITE EMERY WHEELS.



Large Wheels made on Cast Iron Centers if desired. Knife Grinding Wheels a specialty.

Made SOLID of the Celebrated  
**WELLINGTON MILLS EMERY.**

**SUPERIOR TO ALL OTHERS.**

Thousands of manufacturers testify to its being the Strongest, most Durable, and Healthiest Emery Wheel made.

**RUNS WET or DRY.**

**—OUTS COOL and FREE.**

**A SAFE WHEEL.**  
**NEW YORK BELTING & PACKING CO.,**  
Sole Manufacturers.  
Warehouse: 15 Park Row, New York.

## The Original Unvulcanized Packing

**CALLED THE STANDARD.**—As it is the Packing by which all others are compared.  
Accept no packing as JENKINS PACKING unless stamped with our "Trade Mark."

**JENKINS BROS.** 71 John Street, N. Y.  
185 Milk Street, Boston.  
18 So. Fourth St., Phila.  
54 Dearborn St., Chicago.

**IELDS & BROWN**  
Manufacturers and Sole Proprietors of



**For BOILERS and STEAM PIPES**

Reduces Condensation of Steam.

**FOR GAS and WATER PIPES.**

Prevents Sweating and Freezing.

The Best Non-Conductor of Heat and Cold in the World.

Send for Illustrated description Circular, and name, this paper.

143 Worth Street, New York.

78 and 80 Lake Street, Chicago.

**EPPS'S**  
GRATEFUL—COMFORTING.  
**C O C O A**

**To Business Men.**

The value of the SCIENTIFIC AMERICAN as an advertising medium cannot be overestimated. Its circulation is many times greater than that of any similar journal now published. It goes into all the States and Territories, and is read in all the principal libraries and reading rooms of the world. A business man wants something more than to see his advertisement in a printed newspaper. He wants circulation. This he has when he advertises in the SCIENTIFIC AMERICAN. And do not let the advertising agent influence you to substitute some other paper for the SCIENTIFIC AMERICAN, when selecting a list of publications in which you decide it is for your interest to advertise. This is frequently done, for the reason that the agent gets a larger commission from the papers having a small circulation than is allowed on the SCIENTIFIC AMERICAN.  
For rates see top of first column of this page, or address  
**MUNN & CO., Publishers,**  
361 Broadway, New York.

**MUNN & CO., Publishers,**

361 Broadway, New York.

## THE AMERICAN BELL TELEPHONE CO.

95 MILK ST. BOSTON, MASS.

This Company owns the Letters Patent granted to Alexander Graham Bell, March 7th, 1876, No. 174,465, and January 30th, 1877, No. 186,787.

The transmission of Speech by all known forms of Electric Speaking Telephones infringes the right secured to this Company by the above patents, and renders each individual user of telephones not furnished by it or its licensees responsible for such unlawful use, and all the consequences thereof, and liable to suit therefor.

## THE Scientific American Building Edition.

THE SCIENTIFIC AMERICAN ARCHITECTS' AND BUILDERS' EDITION is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming, practically, a large and splendid Magazine of Architecture, richly adorned with elegant plates in color, and with fine engravings; illustrating the most interesting examples of modern Architectural Construction and allied subjects.

A special feature is the presentation in each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with full Plans, Specifications, Costs, Bills of Estimate, and Sheets of Details.

Architects, Builders, and Owners will find this work valuable in furnishing fresh and useful suggestions. All who contemplate building or improving homes or erecting structures of any kind, have before them in this work an almost endless series of the latest and best examples from which to make selections, thus saving time and money.

Many other subjects, including Sewerage, Piping, Lighting, Warming, Ventilating, Decorating, Laying Out of Grounds, etc., are illustrated. An extensive Compendium of Manufacturers' Announcements is also given, in which the most reliable and approved Building Materials, Goods, Machines, Tools, and Appliances are described and illustrated, with addresses of the makers, etc.

The fullness, richness, cheapness, and convenience of this work have won for it the Largest Circulation of any Architectural publication in the world. Sold by all newsdealers.

**MUNN & CO., Publishers,**  
361 Broadway, New York.

## Building Plans and Specifications.

In connection with the publication of the BUILDING EDITION of the SCIENTIFIC AMERICAN, Messrs. Munn & Co. furnish Plans and Specifications for Buildings of every kind, including Public Buildings, Churches, Schools, Stores, Dwellings, Carriage Houses, Barns, etc. In this work they are assisted by able and experienced architects.

Those who contemplate building, or who wish to alter, improve, extend, or add to existing buildings, whether wings, porches, bay windows, or attic rooms, are invited to communicate with the undersigned. Our work extends to all parts of the country. Estimates, plans, and drawings promptly prepared. Terms moderate. Address  
**MUNN & CO.,**  
361 Broadway, New York.

**MUNN & CO.,**

361 Broadway, New York.

## PRINTING INKS.

THE "Scientific American" is printed with CHAS. ENEU JOHNSON & CO.'S INK. Tenth and Lombard Sts., Phila., and 57 Rose St., opp. Duane St., N. Y.